



Tork Universal Wiper 320 Combi Roll



article: 129262

system: W2 - Wipers combi roll system, W1 - Wipers wall/floor/standard system

Layers: 2

Colour: White

Print: no

Embossing: no

Roll Width: 23.5 cm

Roll Length: 340 m

Number of Sheets: 1000

Sheet Length: 34 cm

Roll Diameter: 26 cm

Core Inner Diameter: 7.1 cm

product properties

For general wiping tasks that require strength and absorbency

Economical

Durable and wet strong.

shipping data

consumer unit:

EAN: 7322540174045

pieces: 1

height: 235 mm

width: 260 mm

length: 260 mm

volume: 15.9 dm³

net weight: 2956 g

gross weight: 3037 g

transport unit:

EAN: 7310791188782

pieces: 2

consumer units: 2

material: Plastic

height: 235 mm

width: 520 mm

length: 260 mm

volume: 31.8 dm³

net weight: 5.91 kg

gross weight: 6.11 kg

environmental

Content

Recycled fibres, Chemicals

Material

Recycled fibresRecovered paper can be produced both from collected newsprint, magazines and office waste. The paper is washed with water and treated with chemicals under high temperature



and then filtered. Different fibres demand different processes and this determines the end product properties, and makes the fibre type (recovered or virgin) less important. The environmental benefits and economic feasibility of recovered paper as a raw material source depend on its availability, transport distance and the quality of the collected material. Bleaching of fibres Bleaching is a cleaning process of the fibres and the aim is to achieve a bright pulp, but also to get a certain purity of the fibre in order to achieve the demands for hygiene products and in some cases to meet the requirements for food safety. There are different methods used today for bleaching ECF (elementary chlorine free) where chlorine dioxide is used, and TCF (totally chlorine free) where ozone, oxygen and hydrogen peroxide is used.

Chemicals

The chemicals used in the process as well as the functional chemicals are assessed from an environmental, occupational health and safety and product safety point of view. The used functional chemicals are: Wet strength agent Dry strength agent Dye=if coloured Fixing agents Fluorescent whitening agent Glue=if used Softeners The process chemicals are: Antipitch Protection agent Yankee coating Defoamer Dispersing agents and surfactants pH and charge control Retention aids Broke treatment chemicals Drainage aid

Packaging

Fulfilment of Packaging and Packaging Waste Directive (94/62/EC): Yes Environmental label = Ecolabel This product does not have any ecolabel.

Date of issue 2010-02-25

Revision date

Production

This product is produced at Kostheim mill, Germany, and certified according to ISO 9001:2000, ISO 14001 and EMAS.

Destruction

This product is mainly used for industrial processes and hence it will be contaminated with different substances. This will determine how the used product will be destructed. The product itself is suitable for incineration. Contact local authorities before destruction.