

Puretough P3000 & P3000 3DO

DESCRIPTION

- Industrial protective glove.
- Synthetic textile liner with a synthetic coating.
- Version available with 3 open fingers (middle finger, forefinger and thumb): Puretough P3000 3DO.
- 4 sizes available : 7, 8, 9 and 10.
- Trade unit :12 pairs,144 pairs in a transit case.

CHARACTERISTICS

- Seamless knitted glove, gauge 13.
- Made from high performance and high visible fibres, using Techcor® Knitting Technology.
- Sensitive grey water based mix synthetic compound palm fit coating.
- Water and oil repellent treatment on both liner and coating.
- Silicone-free and DMF-free.

PERFORMANCES

- Excellent comfort and dexterity.
- Lint free glove.
- Good abrasion and blade cut resistance.
- Highly visible yellow liner.
- Water based process environmentally friendly innovative coating.
- In compliance with the standards EN420 (General requirements) and EN388 (Mechanical hazards) by the CTC Centre Technique du Cuir Chaussure maroquinerie.

APPLICATIONS

- For fine tactile handling needing a very good protection against cut.
- Mechanical industries, handling of sharp components.

LIMITATIONS

- Do not use for handling liquids.
- Do not use with a rotating machine in which glove may get caught.



This glove is certified to comply with the essential requirements of European Directive EEC/89/686 of December 21st, 1989 relative to personal protective equipment submitted to CE type examination issued by a notified laboratory, who certifies the conformity of this glove with the EN standards to which it responds and certifies the performance levels obtained during tests.



EN 420

EN 420

5 Dexterity

EN 388

4 Abrasion

3 Cut

3 Tear

2 Puncture



4332

EN 388

Mechanical hazards

Order codes

Sizes	7 (S)	8 (M)	9 (L)	10 (XL)
Puretough P3000	200P30007	200P30008	200P30009	200P30000
Puretough P3000 3DO	200P33DO7	200P33DO8	200P33DO9	200P33DO0