

Hynit™ Intermediate Design

- Top of the range for light-to-medium general applications.
- Special nitrile formulation unites excellent resistance to puncture and abrasion with remarkable flexibility.
- Liquid-repellent impregnation repels oil, grease and dirt.
- The industry standard for small component handling.

Applications

- Appliance manufacture
- Automotive industry: transmission, motor assembly, packaging and inspection
- Can and light materials manufacture
- Component assembly
- Furniture manufacture
- Maintenance
- Packing
- Public utilities
- Shipping and receiving
- Steel mills: general handling
- Textile manufacture: threads, fabrics, mattresses, cables.

Packaging

144 pairs per outer.

Specifications

Ref	Type	Style	EN Size	Length
32-105*	Regular	Slip-on	7, 7.5, 8, 9, 10	215 mm, 235 mm
32-125*	Perforated	Slip-on	7, 7.5, 8, 9, 10	215 mm, 235 mm
32-800	Regular	Safety Cuff	7, 7.5, 8, 9, 10	260 mm, 295 mm
32-815	Cool	Gunn cut pattern	7, 7.5, 8, 9, 10	240 mm (8) 250 mm (9, 10) 260 mm



Features and Benefits

- » **The interlock knit lining and flexible coating stretch to a snug fit.**
Permits excellent dexterity and freedom of movement. Easy to get on and off.
- » **Excellent dry grip.**
Makes handling easier and safer.
- » **Silicone-free.**
Beneficial in the steel and motor industries.
- » **Safely machine-washable.**
More hygienic and longer lasting. Can be economically re-used.
- » **Colour-coded sizes.**
Easy identification ~ especially after washing.
- » **Wide selection of styles, lengths and sizes.**
Allows you to chose the optimum combination of features for your particular application.
- » **Unique Ansell nitrile formulation.**
Superior resistance to cut, puncture and abrasion. Also repels grease and oil.



3111



*32-105, 32-125: fit for special purpose

Ansell Occupational Healthcare

- Wijngaardveld 34C, 9300 Aalst, Belgium
Tel +32 (0) 53 71 05 05; Fax +32 (0) 53 71 13 42; Fax Customer Serv. +32 (0) 53 71 01 81
- Brunel Drive, Newark Industrial Estate, Newark, Nottinghamshire NG24 2EG, England, UK
Tel +44 (0) 1636 605 361; Fax +44 (0) 1636 612 845
<http://www.ansell.be> e-mail: info@ansell.com.au



ISO 9002 Certificate
Number FM 40130