

# HyFlex® 48-130 48-135 (ex SensiLite®)



Mechanical Protection



Special Purpose



Light



## Electrostatic discharge protection

### DESCRIPTION

- HyFlex® 48-130 and 48-135 meet most electrostatic discharge protection needs, providing a comfortable glove at a reasonable price
- The 15-gauge nylon liner provides flexibility and dexterity, while the added carbon fibre offers an economical product-protection solution.
- Comfort and good fit are assured through seamless construction and a wide range of sizes.
- With the palm dipped in a polyurethane coating, HyFlex® 48-130 offers good mechanical resistance and durability.
- The HyFlex® 48-135 is a fingertip-dipped version that allows better fit and flexibility.
- The coated fingertip also prevents the transfer of perspiration to the electronic part
- HyFlex® 48-130 EN 1149-1: Surface resistivity ( $\Omega$ ):  $4.02 \times 10^{10}$  EN 1149-2: Volume resistance ( $\Omega$ ):  $2.19 \times 10^7$  EN 1149-3: Charge decay T50 <0.01 seconds
- HyFlex® 48-135 EN 1149-1: Surface resistivity ( $\Omega$ ):  $1.93 \times 10^{10}$  EN 1149-2: Volume resistance ( $\Omega$ ):  $4.79 \times 10^7$  EN 1149-3: Charge decay T50 <0.01 seconds
- Warning: gloves that provide electro-static discharge protection do not insulate the hands against high-voltage electric current.
- Do not use to handle live wires or for protection against electric current.


### PRODUCT DETAILS

Construction	Knitted
Liner material	Carbon fiber Nylon
Gauge	15
Coating material	Polyurethane
Finishing	48-130: Palm coated 48-135: Fingertip coated
Cuff style	Knitwrist
Colour	White and grey
EN Sizes	6,7,8,9,10,11
Length (mm)	48-130: 205-255 48-135: 190-240
Packaging	12 pairs in a bag; 12 bags in a carton

### IDEAL APPLICATIONS

- Final assembly of dashboard, cables and wires;
- Final assembly of electronic components and mother boards

### PRIMARY INDUSTRIES



### STANDARDS AND CERTIFICATIONS

48-130

EN388:2003 EN388:2016



4131

4131A

48-135

EN388:2003 EN388:2016



113X

113XA

CATEGORY II

### EXTRA FEATURES

48-130



Antistatic



Vending

48-135



Antistatic

Print date 10-07-2018

**Ansell Healthcare Europe N.V. (European Head Office)**

Riverside Business Park, Block J

Boulevard International 55, 1070 Brussels, Belgium

Tel. +32 (0) 2 528 74 00 • Fax +32 (0) 2 528 74 01 • Fax Customer Service +32 (0) 2 528 74 03

<http://www.ansell.eu> • E-mail [info@ansell.eu](mailto:info@ansell.eu)