

# HyFlex® 11-518

MECHANICAL PROTECTION

 CUT PROTECTION

 LIGHT

STYLE #	CONSTRUCTION	GAUGE	LINER MATERIAL	COATING MATERIAL	FINISHING	CUFF STYLE	COLOUR	EN SIZE	LENGTH MM	PACKAGING
11-518 	Knitted	18	Spandex Nylon Dyneema® Diamond Technology	Polyurethane	Palm coated	Knitwrist	Blue	6, 7, 8, 9, 10, 11	210-265	12 pairs in a bag, 12 bags in a carton



## Ultralight duty cut resistant glove

### PRIMARY INDUSTRIES



### IDEAL APPLICATIONS

- Final assembly
- Handling & assembly of small or ultra-fine sharp parts
- Injection molding parts assembly
- Machining -special metal blends
- Packaging areas with risk of cut
- Stamping - light & dry
- Wire assembly & fastening




### DESCRIPTION

- The first 18-gauge glove with EN Level 3 cut protection, and EN Level 3 abrasion protection for extended glove life.
- Dyneema® Diamond Technology fibre and a thin PU coating bring a new degree of dexterity and tactility for applications with cut risks.
- An ultralight fabric and tailored fit, including D3 Pinky Knitting, create a sensation of barehand contact.
- The soft ultralight-duty seamless liner breathes to keep hands cool and dry, and offers enhanced flexibility and fingertip sensitivity with superior comfort
- Comprehensive 6-11 sizing ensures optimum fit and comfort for every worker.
- In field trials the HyFlex® 11-518 was preferred by nearly 70% of workers over thicker gloves, a preference that correlates with compliance.

### FEATURED TECHNOLOGY

Dyneema®  
Diamond  
Technology



**CATEGORY II**

Print date: 03-02-2018

**Ansell Healthcare Europe N.V. (European Head Office)**

Riverside Business Park, Block J

Boulevard International 55, 1070 Brussels, Belgium

Tel. +32 (0) 2 528 74 00 • Fax +32 (0) 2 528 74 01 • Fax Customer Service +32 (0) 2 528 74 03

<http://www.ansell.eu> • E-mail [info@ansell.eu](mailto:info@ansell.eu)

