

Extended, chemical-resistant disposable neoprene gloves, with superb wet and dry grip performance

- **Specialized protection:** Provides strong chemical splash protection from most acids and alcohols and EN 374 Type B chemical resistance certification
- **Strong grip:** Textured fingertips and neoprene material enhance grip performance in wet and dry environments
- **Reduced allergy risk:** Non-latex formulation prevents Type 1 (latex) allergic reactions
- **Easy donning:** Polymer-coated, these MICROFLEX[®] gloves are easy to don
- **Extended protection:** MICROFLEX[®] NeoTouch[™] 25-201 gloves' extended cuff also provides greater forearm and wrist protection



Industries

- Life Sciences
- Chemical

Recommended For

- Transferring liquids and solids
- Sample taking and processing
- Testing

TECHNICAL DATA SHEET

	Product Information
Material	Neoprene (Polychloroprene)
External Glove Surface	Textured Fingers
Audit Standards	ISO 13485
Product Certification	ASTM D6977, CE 0493, EN 421:2010, EN ISO 21420:2020, EN ISO 374-1:2016 Type B KPT, EN ISO 374-5:2016 Virus, ISO 13485, UKCA, FDA21 CFR 177-2600-US Food Contact Approved, Please consult the IFU
Packaging Overview	100 gloves per dispenser 10 dispensers per case 1000 gloves per case
Storage Instructions	Keep out of direct sunlight; store in a cool and dry place. Keep away from sources of ozone or ignition.
Country Of Origin	Indonesia
Product Segmentation	High Risk
Antistatic	Yes EN1149
Silicone Free	No
Vulcanization Chemical Accelerators	Zinc Diethyldithiocarbamate <i>Only a very small number of users may be sensitive to this ingredient(s) and hence may develop irritant and/or allergic contact reactions.</i>

PHYSICAL PROPERTIES

	Typical Values		Testing Method
Length (mm/inches)	285 / 11.2		ASTM D3767,EN 420
Freedom from Holes (Inspection level I)	1.5 AQL		ASTM D5151,EN 455-1
Palm Thickness (mm/mils)	0.13/ 5.1		ASTM D3767,EN 420
Finger Thickness (mm/mils)	0.16/ 6.3		ASTM D3767,EN 420
	BEFORE AGING	AFTER AGING	
Ultimate Tensile Strength (MPa)	≥ 14	≥ 18	ASTM D412 & D573
Elongation at Break (%)	≥ 700	≥ 600	ASTM D412
Force at break (N)	≥ 3.6	≥ 3.6	

ORDERING INFORMATION

Size	S (6.5 - 7)	M (7.5 - 8)	L (8.5 - 9)	XL (9.5 - 10)
Product Code	25201070	25201080	25201090	25201100

Performance Standards and Regulatory Compliance



For additional information visit us at www.ansell.com, or call us at

Europe, Middle East & Africa Region
Ansell Healthcare Europe NV
T: +32 (0) 2 528 74 00
F: +32 (0) 2 528 74 01

Asia Pacific Region
MY: +603 8310 6688
apac.medical@ansell.com
CN: +86 21 38275000
infochina@ansell.com
JP: +813 5549 8151
info.medical.jp@ansell.com

North America Region
Ansell Healthcare Products LLC
T: +1 800 800 0444
F: +1 800 800 0445

Latin America & Caribbean Region
BR: +55 (11) 3356-3100
latam.medical@ansell.com
MX: +52 442 296 2050
latam.medical@ansell.com
CO: +57 1 288 3247
latam.medical@ansell.com

Australia
Ansell Limited
T: +61 1800 337 041
F: +61 1800 803 578

Russia
Ansell PYC
Ten. +7 495 258 13 16

Ansell, ® and ™ are trademarks owned by Ansell Limited or one of its affiliates. US Patented and US and non-US Patents Pending: www.ansell.com/patentmarking © 2025 Ansell Limited. All Rights Reserved.

Neither this document nor any other statement made herein by or on behalf of Ansell should be construed as a warranty of merchantability or that any Ansell product is fit for a particular purpose. Ansell assumes no responsibility for the suitability or adequacy of an end user's selection of gloves for a specific application.

