

Product datasheet

uvex 1 business 8427 1-3

Safety boot DIN EN ISO 20345:2022 S3L FO SR

Sizes: 39 - 52 | Width: 10, 11, 12



AREA OF APPLICATION

The light application covers all areas in which work is carried out indoors in particular and which do not place high demands on the physical properties of the outsole of a safety shoe.

OUTSOLE

Polyurethane outsole



- PU outsole
- antistatic
- short-term heat-resistant up to 120°C
- excellent slip resistance (**SR**)
- oil- and fuel resistant (**FO**)
- free of silicones, plasticisers and other substances that interfere with wetting agents



FEATURES

Upper material	• breathable microvelour (clima zone) • water-repellent (WPA) • suitable for people allergic to chrome
Lining material	• breathable textile
Fastening	• laces
Comfort	• soft padding on collar
Innersole	• removable comfortable innersole

PROTECTIVE FEATURES

Toe cap	• steel protective toe cap
Penetration resistance	• metal-free, textile penetration resistance

CERTIFICATES

uvex medicare	• certified for orthopaedic innersoles according to the description in DGUV 112-191
100% vegan	• certified free from animal ingredients and products • additional protection for people with allergies and intolerances
ESD	• protection against electrostatic charge according to EN 61340-4-3 und EN 61340-5-1

SUSTAINABILITY

Recycled/sustainable materials	• removable innersole and heel cap made wholly or partly from recycled materials • free from harmful substances in accordance with the uvex restricted substances list
--------------------------------	---

ACCESSORIES/ SPARE PARTS

Replacement innersole	• 9515 7-9
Laces	• black 9599700