

RO23095 Flamebuster2 Nordic Coverall

stitched

TICKING ALL BOXES

PROTECTION LEVEL: ARC 2

10.2 cal/m²

Above shown is the ATPV value.

Possibility to

place shoulder pads

BODY BURN INJURY PREDICTION

4.4%

Body burn prediction of 2nd + 3rd degree burn

EN SAFETY STANDARDS







EN ISO 11611:2015



EN ISO 13688:2013

EN ISO 11612:2015 A1 A2 B1 C2 D0 E3 F1 (A1=50 washing cycles)










ISO 6330:2012

Body burn injury prediction



Above shown body burn scores are without FR underwear. Visit www.roots-original.com/burn-injury-predictions for more information.

QUICK DETAIL OVERVIEW



Regular: 31" Tall:

 $33^{\prime\prime}$ (standard size)



Flamebuster2 Nordic Coverall

FEATURES & BENEFITS

Flame retardant retroreflective tape > Stay visible in any situation

Fully non-metallic > Virtually indestructable materials

Central YKK zipper > Easy to open and close

2 Chest pockets with YKK zip > Double storage space

2 Back pockets with flap > More storage

2 Side pockets with trouser access > Easy access

Rule pocket on right leg > Always space for a ruler

Pen pocket with flap on left sleeve > Keep a pen on you at all times

2 radio / gas detector loops > Keep your instruments within reach

2 tier knee pockets > Place for your kneepads

Possibility to place shoulder pads > Less strain on the shoulders

Garment fit for industrial laundry > ISO 15797 - 75°C

Garment fit for domestic laundry > ISO 6330 - 60°C

KEY FEATURES













FABRIC INFORMATION

Fabric composition

FLC320 - 80% cotton / 19% polyester / 1% antistatic

Fabric weight

FR Fabric Type

320 g/m²

Treated

Additional certification

Logo





Certified for logo applications

- Oeko-Tex Standard 100
- AS/NZ 4399:1996 Sun protective clothing UPF 50+ (Excellent Protection)

Please visit www.roots-original.com/certificates to download all relevant certificates.

Product care instructions

To preserve the fabrics strength and protective capacity, we strongly advice to follow our detailed care instructions.

- Always launder with coverall zippers closed.
- 2 Remove all tools from pockets
- Rinse properly after wash.
- 4. Never wash flame retardant clothing with detergents containing bleach.
- After washing, tumble dry at 50°C to avoid excessive 5. shrinkage.
- Do not iron directly over heat seal logos.





Whenever in doubt or in need of advice, ask your dry cleaner or contact us. We are here to help or visit **www.roots-original.com/product-care**



YOUR ARC FLASH PROTECTION SPECIALISTS

Get in contact, we'd love to help you!

Give us a call on +31 (0)10 2955 955 or drop us a message at: info@roots-original.com