

Warwick

892VC2PIP



SIO-SAFETM EXTRA LIGHT

Hi-vis coverall with ARC protection

Protect yourself thoroughly while performing activities with a risk of an arc flashover. Our hi-vis Warwick coverall with straight collar and double stitched flame retardant reflective striping has sufficient storage space with 2 patched chest pockets, 2 patched slanted pockets, 1 ruler pocket, 1 back pocket, 1 thigh pocket, 1 inside pocket and 2 loops for gas detectors. Adjust the coverall for a perfect fit by means of sleeve narrowing by press studs and the adjustable elasticated waist. The coverall complies with many norms like IEC 61482-2, EN ISO 11612, EN ISO 11611, EN ISO 14116, EN1149-5, EN 13034 and EN ISO20471.















Hi-vis coverall with ARC protection

Interior:

» 1 inside pocket

» Adjustable elasticated waist

Warwick - 892VC2PIP

European Standards: (based upon size L)

» EN61482-2: 2020 APC1- ELIM 7 cal/cm² - ATPV 8 cal/cm²

» EN ISO 11612: 2015 / A1 B1 C1 F1 » EN ISO 11611: 2015 / Class 1 - A1

» EN 1149-5 : 2018

» EN 13034 : 2005 + A1 : 2009 Type 6 » EN ISO 20471: 2013 +A1 2016 / Class 3

» EN ISO 13688 : 2013 +A1 : 2021

Fabriekstraat 23

B-8850 Ardooie Belgium

Exterior:

- » Straight collar
- » Zip closure under flap with concealed press studs » Identification label
- » 2 patched chest pockets with flap closed by concealed press studs
- » 2 patched slanted pockets with flap closed by concealed press studs
- 2 loops for gas detectors
- 1 ruler pocket with flap closed by concealed press studs
- 1 back pocket with flap closed by concealed press studs
- 1 patched thigh pocket with flap closed by hidden press studs
- 2 side slits
- » Round sleeves
- » Sleeve narrowing by press studs
- » Knee pockets
- Double stiched (2x2) flame retardant reflective striping (50mm)

Sio-Safe[™] Extra Light: 57% aramid + 42% polyester + 1% AST; ± 260 g/m²

Sizes:

EUR: Short: 48 - 58 Regular: 44 - 64 Long: 46 - 60

Colour:

» FC1 Hi-vis orange

Packaging:

5 pieces per box

Wash and care instructions:











SIOEN head office

T: +32 (51) 740 800 F: +32 (51) 740 962 www.sioen-ppc.com



our products