



Warwick

Coveralls, ARC protection (APC1), high-vis class 3

892VC2PIP

Protect yourself thoroughly while performing activities with a risk of an arc flashover. Our hi-vis Warwick coverall with straight collar and double stitched flame retardant reflective striping has sufficient storage space with 2 patched chest pockets, 2 patched slanted pockets, 1 ruler pocket, 1 back pocket, 1 thigh pocket, 1 inside pocket and 2 loops for gas detectors. Adjust the coverall for a perfect fit by means of sleeve narrowing by press studs and the adjustable elasticated waist. The coverall complies with many norms like IEC 61482-2, EN ISO 11612, EN ISO 11611, EN ISO 14116, EN1149-5, EN 13034 and EN ISO20471.

Colours

- High-vis orange (FC1)


EU Size

- short: 48-58
- regular: 44-64
- long: 46-60



- Breathable fabric
- Kneepad pockets: bottom-loading
- Lightweight
- Inherently flame-retardant

Certification



Specific certification: outer jacket including detachable lining

Attention: this certification only applies to **size 52 - regular** in **colour High-vis orange**. Select another size and/or colour to consult the corresponding certificates.

- EN 61482-2 : 2020 APC1- ELIM 7 cal/cm² - ATPV 8 cal/cm²
- EN 13034 : 2005 + A1 : 2009 Type 6
- EN ISO 11612 : 2015 / A1 B1 C1 F1
- EN ISO 11611 : 2015 / Class 1 - A1
- EN 1149-5 : 2018
- EN ISO 20471 : 2013 +A1 2016 / Class 3
- RIS 3279 TOM 2016
- EN ISO 13688 : 2013 +A1 : 2021

Material

- Sio-Safe™ Extra Light: 57% aramid + 42% polyester + 1% AST; ± 260 g/m²

Wash & care



Exterior

- Straight collar
- Zip closure under flap with press studs
- 2 loops for gas detector
- 2 patched chest pockets under flap with press studs
- 1 patched thigh pocket with flap
- 1 patched back pocket under flap with hidden press studs
- 1 ruler pocket under flap with hidden press studs
- Kneepad pockets
- 2 slanted patched pockets under flap with hidden press studs
- 2 side slits with hidden press studs
- Round set-in sleeves
- Sleeve narrowing by press studs
- Elasticated waist
- 2 needle stitched flame retardant reflective striping (50 mm)

Interior

- 1 inside pocket
- Identification label