

P.O. Box 21, Waverley Street, Hull. HU1 2SJ Tel: 01482 222522 www.arco.co.uk

ECONOMY MOULDED DISPOSABLE RESPIRATOR - SINGLE SHIFT USE FILTERING HALF MASK TO PROTECT AGAINST PARTICLES

PRODUCT DATA

1. <u>General:</u>

- 1.1 Product Ref.'s **1A0100 1A0200**
- 1.2 Standard EN 149:2001+A1:2009
- 1.3 Classification FFP1 NR D

2. PRODUCT DESCRIPTIONS:

- 2.1 **1A0100** Single shift use particulate respirator.
- 2.2 **1A0200** Single shift use valved particulate respirator.
 - Features exhalation value to reduce temperature and humidity within the respirator and improve exhalation resistance.

3. PROTECTION:

For protection against non-toxic solid and liquid aerosols, [e.g. oil-mists], in concentrations up to 4 x WEL, [Workplace Exposure Limit].
i.e. APF, [Assigned Protection Factor] = 4.

4. APPLICATIONS:

4.1 Recommended applications include;- textile industry, craft work, iron and steel industry, mining, underground civil engineering and woodwork (except hardwood), etc..

5. MATERIALS:

5.1 Outer Layer: Polyester Fabric 5.2 Filter Media: High Filtration Efficiency Melt-Blown [Polypropylene] 5.3 Inner Layer: Polypropylene Non-Woven 5.4 Nose Pad: Polyethylene [PE] Foam 5.5 Headband: Latex-Free Synthetic Rubber Headband Staple: Zinc Metal Wire 5.6 5.7 Exhalation Valve: Valve Housing - Polypropylene Valve Membrane - Silicon Rubber [Note: 1A0200 model only]



P.O. Box 21. Waverley Street, Hull. HU1 2SJ Tel: 01482 222522 www.arco.co.uk

ECONOMY MOULDED DISPOSABLE RESPIRATOR - SINGLE SHIFT USE FILTERING HALF MASK **TO PROTECT AGAINST PARTICLES**

PRODUCT DATA

6. DIMENSIONS:

- 6.1 Respirator:
- 6.2 Nose Pad:
- 6.4 Headband: Upper Lower 6.3 Exhalation Valve:

135mm x 128mm x 55mm [L x W x H] 118mm x 30mm x 1.5mm [L x W x T] 41.3mm x 38.2mm x 12.1mm [L x W x H] 300mm x 5mm x 0.55mm [L x W x T] 265mm x 5mm x 0.55mm [L x W x T]

7. CERTIFICATION:

These particulate respirators are EN149:2001+A1:2009 FFP1 NR D certified single-use disposable respirators with CE certification according to European Council Directive 89/686/EEC and subsequent amendments.

[Note: These respirators pass the optional EN149 Dolomite [D] clogging test with the mark "D" on products.]

EC-Type Examination is certified by BSI [British Standards Institution] with the CE notified body number 0086.