TECHNICAL SPECIFICATION

Typhoon™ Moulded Mask FFP2 Valved (725)

Box of 10 / BEP120-001-A00

DESCRIPTION

Moulded mask featuring our unique Typhoon™ Valve technology for extremely low exhale breathing resistance, and low CO2, heat and moisture build up.

- Medium efficiency (94% minimum) filtering

OPTIONS

Box of 10 (BEP120-001-A00)

SAFETY STANDARDS

EN 149

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

SPECIFICATIONS

Classification
FFP2 (Filtering Facepiece Particulate)

Usage
NR (Non-Reusable)

Minimum Filtration Efficiency
94% For FFP2 Rated

Nominal Protection Factor
12

Mask Design
Moulded

Toggle Harness adjustment system
Yes

Latex free
Yes

Mask Material
Polypropylene

BSI Kitemark
Yes

Face Fit Testing Required
Yes

Filter Type
P (Protects Against Solid and Liquid Aerosols)

Activated Carbon Layer
No

Maximum Total Inward Leakage (TIL)
8%

UK Assigned Protection Factor
10

Exhalation Valve
JSP Typhoon Valve

Nose Bridge
Adjustable Aluminium

Metal Free
No

Filter Shelf Life
5 Years

Product Weight
21g

FEATURES

Comfort

A 360° comfort foam area around the inside of the mask provides a perfect fit and maximum resistance.

Fit

The welded nose piece prevents any irritation, misshaping and gives a tighter fit. Adjustable strap means it can be fitted comfortably to all head sizes and shapes.



Typhoon™ Valve

The Unique Typhoon™ valve has been designed to reduce breathing resistance, heat and moisture build-up. The valve is unaffected by any moisture, and therefore can be used with the same performance under very low temperatures.

RANGE

DOWNLOADS

Image Pack (ZIP)
doc-olympus-700-series-725.pdf (PDF)

JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.