

TECHNICAL SPECIFICATION



PressToCheck™ A2 P3 Filters

Pack of 2 / BMN740-000-600



DESCRIPTION

PressToCheck™ is the easiest way to face-fit check the seal of your respirator, every time you put it on! The range features HEPA filtration exceeding 99.95%, Low profile design maximising compatibility and low breathing resistance across the range.

F-4123 A2P3 organic gas / vapour + dust replacement encapsulated filters, featuring PressToCheck™ technology for daily face-fit reassurance.

Winner of the BSIF Product Innovation Award.

OPTIONS

Pack of 2 (BMN740-000-600)

SAFETY STANDARDS

EN 14387



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.







Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 1 of 2 / Issued 19 Feb 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.



SPECIFICATIONS

| | | |
|--|---|--|
| Classification A2P3 |  | Filter Type Organic Vapours, Nuisance Odours and Particulate |
| Usage R (Reusable) |  | (D) Resistance to dust clogging Yes – D marking = passes optional clogging test |
|  Activated Carbon Filter Yes | | Minimum Filtration Efficiency 99.95% For P Rated |
| Maximum Total Inward Leakage (TIL) 2% when fitted to Force8 Half Mask | | Maximum Total Inward Leakage (TIL) 0.05% when fitted to a Force10 Full Face Mask |
| Nominal Protection Factor 12 When Fitted To A Force8 Half Mask | | Nominal Protection Factor 1000 When Fitted To A Force10 Full Face Mask |
| UK Assigned Protection Factor 10 When Fitted To A Force8 Half Mask | | UK Assigned Protection Factor 20 When Fitted To A Force10 Full Face Mask |
|  Type Press To Check Technology | | Latex free Yes |
| Metal Free Yes | | Filter Material Pleated Media & Activated Carbon |
| Filter Casing Material ABS | | Filter Shelf Life 10 Years |
|  BSI Kitemark Yes |  | Product Weight 231g Per Pair |




FEATURES



Increased Product Life

PressToCheck™ encapsulated filters offer ultimate longevity – the durable design makes the filters easy to clean and reuse. Correct cleaning, maintenance and storage increases the useful life of the product.

VIDEOS

-  youtu.be/1Y9G8E9kEXQ
-  youtu.be/Ecyu_ftPPX4
-  youtu.be/-oUSyP9_NsA

DOWNLOADS

-  [Image Pack \(ZIP\)](#)
-  [doc-force-press-to-check-filter-f-4123.pdf \(PDF\)](#)



JSP Limited, Worsham Mill, Minster Lovell, Oxford OX29 0TA, England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824111 / Email: sales@jgpsafety.com / Web: www.jgpsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jgpsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.

Page 2 of 2 / Issued 19 Feb 2026 / Copyright 2018 - 2026. JSP Limited. All Rights Reserved.

