

# TB Davies Extra Heavy Duty Mobile In Red With Expamet Tread



[Representative image of product]

# **Specifications**

Warranty: 1-year
Max Load: 150kg
Standard: BS EN131-7
Material: Mild Steel
Commodity Code: 73269030

Country of Origin: GBRecommended Usage: Intensive

### **Common Dimensions**

- Rung Depth: 0mm

- Distance Between Rungs: 0mm

- Handrail Height: 0mm

# **Availability & Delivery**

(See exceptions, if applicable, overleaf)

#### **Product Description**

Suitable for the most demanding projects and applications, constructed from box section steel on a splayed base to provide much greater stability and strength. Over tested to 200kg. The treads are available in either expamet or ribbed rubber depending on your requirements. Kite-marked to the demanding EN131-7 British Standard.

#### **Features**

- Extra wide 490 x 180mm deep treads for comfort and safety
- Large 500 x 560mm platform with intermediate guardrails and toe boards
- Fully welded steel box-section construction
- Additional bracing for more frequent use applications
- Choice of ribbed rubber or expamet treads
- Locking device and anti-ascent bar
- Easy one-user manoeuvrability on 200mm diameter heavy-duty wheels and 100mm swivel castors
- EN131-7

### **Product Dimensions**

SKU	Treads	Platform Height	Approx. Working Height <sup>1</sup> (mm)	Height (mm)	Width (mm)	Depth (mm)	Nett Weight (kg)
2026-003	3	690	2290	1690	955	780	48.0
2026-004	4	920	2520	1920	1120	850	56.0
2026-005	5	1150	2750	2150	1290	910	62.0
2026-006	6	1380	2980	2380	1425	960	81.0
2026-007	7	1610	3210	2610	1610	1010	89.0
2026-008	8	1840	3440	2840	1790	1060	99.0
2026-009	9	2070	3670	3070	1955	1140	109.0
2026-010	10	2300	3900	3300	2130	1220	124.0
2026-011	11	2530	4130	3530	2290	1270	132.0
2026-012	12	2760	4360	3760	2400	1270	143.0
2026-013	13	2990	4590	3990	2560	1370	153.0
2026-014	14	3220	4820	4220	2730	1540	165.0
2026-015	15	3450	5050	4450	2890	1565	177.0

<sup>&</sup>lt;sup>1</sup> Working height is calculated as 1,600mm plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of 75° degrees. Note that 10 tread and above are supplied in 2 sections, which require bolting together before first use.

## **Shipping Dimensions**

SKU	Barcode	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m³)	Gross Weight (kg)
2026-003	5060356918270	1690	955	780	1.259	48.0
2026-004	5060356918287	1920	1120	850	1.828	56.0
2026-005	5060356918294	2150	1290	910	2.524	62.0
2026-006	5060356918300	2380	1425	960	3.256	81.0
2026-007	5060356918317	2610	1610	1010	4.244	89.0
2026-008	5060356918324	2840	1790	1060	5.389	99.0
2026-009	5060356918331	3070	1955	1140	6.842	109.0
2026-010	5060356918348	3300	2130	1220	8.575	124.0
2026-011	5060356918355	3530	2290	1270	10.266	132.0
2026-012	5060356918362	3760	2400	1270	11.46	143.0
2026-013	5060356918379	3990	2560	1370	13.994	153.0
2026-014	5060356918386	4220	2730	1540	17.742	165.0
2026-015	5060356918393	4450	2890	1565	20.127	177.0

Packaging Material: No Packaging

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed.

This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.