

Safety spectacle. Single piece polycarbonate frame suitable for over-spectacle use.

## SPECIAL FEATURES

- ✓ Can be worn over spectacles
- ✓ Adjustable and inclinable temples
- ✓ Ventilated temple tips and side shields
- ✓ Brow protection
- ✓ Anti-scratch and Anti-fog lens
- ✓ UV400 protection
- ✓ Ideal to be worn by site visitors



VERSIONS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
CLEAR	○ RLY00461	2C-1.2 e 1FT CE / Z87+ U6	e EN 166 FT CE / Z87+	Impacts, UV radiations	Riley Anti-scratch and Anti-fog
GREY	● RLY00462	5-2.5 e 1FT CE	e EN 166 FT CE	Impacts, UV and Solar radiations	

See overleaf for this product's technical specification →

## GENERAL SPECIFICATION

LENS BASE	2mm
WEIGHT	42g

## PACKAGING

Individually contained in a polythene bag with a Eurosot

PER BOX	10
PER CARTON	200

## COMPONENT SPECIFICATION

COMPONENT	MATERIAL	FEATURES
LENS AND NOSE BRIDGE	Polycarbonate	Single piece, moulded with side protection
TEMPLE	Polycarbonate / Thermoplastic Elastomers (TPE)	Co-injected - Flexible and comfortable
HINGE	Metal	Durable

## LENS MARKINGS (CE)

### LENS FILTER TYPE:

2C UV  
5 Solar

### SCALE NUMBER (SHADE):

1.2 Clear or Amber  
2.5 Grey

Identity of the manufacturer

### OPTICAL CLASS:

1 High optical quality

### MECHANICAL STRENGTH:

F Low energy impact, resists a 6mm, 0.86g ball at 45m/s  
T Protection against high-speed particles at extreme temperatures

Certification mark

## FRAME MARKINGS

Identity of manufacturer

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

### MECHANICAL STRENGTH:

F Low energy impact, resists a 6mm, 0.86 g ball at 45m/s  
T Protection against high-speed particles at extreme temperatures

Certification mark

## USA (ANSI)

### LENS

U6 UV (Clear, Amber, Blue)  
L1.7 Solar (I/O, Twilight)  
L2.5 Solar (Grey)

### LENS AND FRAME:

Z87+ High velocity impact, 0.25 inch, 1.04g ball at 150ft/s

## CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

## PART OF THE GLOBUS GROUP

Based on a substantial heritage of successfully protecting hands, Globus has grown to become one of the world leaders in worker safety, leading the way in technical innovation to provide a range of products that have set the standard for safety, productivity and wearer acceptance.

This focus on creating cutting edge personal protection solutions has now extended to eye and face protection with Riley; a new collection of high performance protective eyewear products engineered with innovation and ingenuity, designed for optimum comfort and styled for safe working.

Riley product approval certificates to CE standards will be provided on request. Riley is a registered trademark.

[www.riley-eyewear.com](http://www.riley-eyewear.com)

E: [info@riley-eyewear.com](mailto:info@riley-eyewear.com)

T: +44 (0)161 877 4747

F: +44(0)161 877 4746

Globus (Shetland) Ltd, 14 Central Park, Mosley Road, Manchester, M17 1NY, UNITED KINGDOM

