Cordless Rotary Hammer Drill & Driver EY78A1LJ2G / EY78A1PN2G / EY78A1X

Overview







Cordless Rotary Hammer Drill & Driver

- New high-performance 5.0Ah Li-ion battery pack*
- 65min. usable and 80min. full charging
- Light weight 2.6kg (incl. battery)*
- Dual function: Rotary Hammer or Drill & Driver
- 5 stage torque clutch plus drill position
- 'T shape' design for improved balance and ergonomics
- Drill chuck SDS-plus
- Electric speed control
- Electric brake
- Reversible
- Bit adapter
- Incl. second battery pack*

Model / Type	EY78A1LJ2G	EY78A1PN2G	EY78A1X
Voltage	18V	18V	18V / 14.4V
Battery capacity accord. to IEC (technology)	5.0Ah (Li-Ionen)	3.0AH (Li-lonen)	*
Charging time (usable / full charging)	65 / 80min.	45 / 60min.	*
Speed at no load in rpm	0 - 1.250min-1 (rpm)	0 - 1.250min-1 (rpm)	*
Blows per minute	0 - 4.750	0 - 4.750	*
Drill chuck	SDS-plus	SDS-plus	*
Size (W x L x B)	64 x 249 x 272mm	64 x 249 x 264mm	*
Weight (incl. battery)	2.55kg	2.40kg	*
Standard accessories	2 x battery EY9L54B charger EY0L82B incl. plastic box	2 x battery EY9L53B charger EY0L82B incl. plastic box	without battery without charger without plastic box

X-type (EY78A1X) without battery and charger.

Battery capacities							
Voltage				18V	14.4V		
Model				EY78A1LJ2G	EY78A1PN2G		
Battery				EY9L54B(LJ)	EY9L53B(PN)		
Drilling + Fastening	Concrete screw	Holes in concrete and screws fastened	Ø 3.5mm x 30mm Ø 4mm x 25mm	230 pcs/charge	140 pcs/charge		
	Plastic anchor Fastening application	Holes in concrete and screws fastened	Ø 6mm x 30mm Ø 4.5mm x 25mm	170 pcs/charge	100 pcs/charge		
Drilling	Holes in concrete		Ø 3.5mm x 30mm	230 holes/charge	170 pcs/charge		
			Ø 8mm x 30mm	150 holes/charge	90 holes/charge		
			Ø 10mm x 40mm	100 holes/charge	60 holes/charge		
			Ø 12.5mm x 40mm	50 holes/charge	30 holes/charge		
			Ø 16.5mm x 40mm	17 holes/charge	10 holes/charge		