



RoHS
Compliant



Specifications

Rated Voltage	: 250V
Normal Work Voltage	: 187V to 275V
Frequency	: 50 (Hz)
Rated Current	: 13 A
Polarity Number	: Live, Zero, Ground (Pole)
Rated Leakage Tripping Current	: 30mA
Rated Leakage No Tripping Current	: 15mA
Max Tripping Time	: ≤0.1 Minute
Operation Temperature	: -5°C to +40°C
Air Relative Degree of Humidity	: ≤93% (25°C)

Dimension



Dimensions : Millimetres

Note:

For indoor and outdoor use

Attention: 1) Make sure the button of test can be tripped before use it, otherwise please stop use it.

2) The "Test" button and "Reset" button Can't be use as "on-off" switch for line.

Part Number Table

Description	Part Number
RCD Plug in	PEL00413

Important Notice : This data sheet and its contents (the "Information") belong to the members of the Premier Farnell group of companies (the "Group") or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted. The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error in or omission from it or for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence. pro-ELEC is the registered trademark of the Group. © Premier Farnell Limited 2016.