

Novaflex 6300 Food S&D Hose

Specification Sheet

Product Code: 39632--

For further information:

Arco Ltd, PO Box 21, Waverley Street, Hull, HU1 2SJ

hose@arco.co.uk

www.arco.co.uk

Tel: 01482 383280

Fax: 01482 591450



An FDA grade suction & discharge hose for the transfer of food and liquid.

Construction: Lining – FDA grade white nitrile rubber
Reinforcement – multiple plies of polyester synthetic textile, and wire helix
Cover – blue nitrile rubber

Applications: Suction and delivery of fatty foods and liquids

Properties: Not to be used for continuous steam service
Flexible and rugged
Odourless and taste free
Built on special stainless steel mandrels for cleanliness
Meets REACH, ADI, FDA, USDA & 3A sanitary standards Authorized # 1376

Temperature range: -40°C to +99°C, cleaning in place to +120°C

Standard length: 30 metre

I.D. (mm)	O.D. (mm)	Working Pressure		Bend radius (mm)	Vacuum (mmHg)	Weight (kg/m)	Code
		(bar)	(psi)				
19.05	31.8	10	150	101	675	0.60	3963219
25.4	38.1	10	150	127	675	0.74	3963225
38.1	50.8	10	150	152	675	1.06	3963238
50.8	63.5	10	150	177	675	1.41	3963251
76.2	89.4	10	150	228	675	2.25	3963276
101.6	114.8	10	150	304	675	2.95	

All pressure ratings quoted at ambient temperature