

# AXIS

## SPORTS-INSPIRED

Available with Contrast coating, AXIS offers protection adapted to each user thanks to its pivoting temples and it considerably reduces eye strain.



AXPSI



AXPSF



AXCONT



Adjustable non-slip bridge












28 g

- + UPPER PROTECTION**
- + PIVOTING TEMPLES**
- + NON-SLIP TIPGRIP TEMPLES**
- + ADJUSTABLE NON-SLIP BRIDGE**
- + ANTI-STATIC**

**bolle**  
SAFETY

# AXIS

## SPORTS-INSPIRED

MODEL	VERSIONS	REFERENCES	LENS MARKING	FRAME MARKING	COATINGS
AXIS	 Clear	AXPSI	2-1,2  1 FT C€	 EN166 FT C€	Anti-scratch/Anti-fog
	 Smoke	AXPSF	5-2,5  1 FT C€	 EN166 FT C€	Anti-scratch/Anti-fog
	 Contrast	AXCONT	5-1,1/1,4  1 FT C€	 EN166 FT C€	Anti-scratch

### LENS MARKING


#### Optical class symbols:

1. Continuous work

#### Mechanical strength symbols:

- F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.
- T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

#### Others symbols:

C€ European standard  Manufacturer name

### FRAME MARKING

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

**F.** Low energy impact, resists a 6 mm, 0.86 g ball at 45 m/s  
Maximum protection for glasses.

**T.** The letter T, immediately after the mechanical strength symbol, authorises use for high speed particles at extreme temperatures.

C€ European standard  Manufacturer name

**Bollé Safety product approval certificates to CE standards will be sent on request.**

### TECHNOLOGY

#### B-CONTRAST

a revolutionary coated, gradient lens offering better long term eye comfort. B-Contrast is particularly suited to wearers of safety glasses with clear lenses.

B-Contrast filters 99.99% of UVA/UVB up to 400 nm and over 30% of blue light.

### CLEANING AND STORAGE

**CLEANING:** The lenses should be cleaned regularly. Bollé Safety recommends only using the B-clean lens cleaning system.

**MAINTENANCE:** Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the complete product. After each use it is recommended to keep the spectacles or goggles in a microfiber pouch or rigid case.

**STORAGE:** All products must be stored in a dry and clean environment.

PACKAGING AND EAN13 CODE			
	AXPSI	AXPSF	AXCONT
Individual plastic bag	3660740002923	3660740002930	3660740002947
10 safety spectacles per inner box	3660740102920	3660740102937	3660740102944
300 safety spectacles per outer pack	3660740202927	3660740202934	3660740202941

CHARACTERISTICS	
LENSES	PC - 2,4 mm - Curve 10,5
FRAME	PC
TEMPLES	PC + TPR
STRAP	Non applicable
FOAM	Non applicable
SPARE LENSES	No



01/10/2013

Europe Bollé Safety  
95 rue Louis Guérin  
69100 Villeurbanne - France  
Tél. : 00 33 (0) 4 78 85 23 64  
Fax : 00 33 (0) 4 78 85 28 56  
contact@bolle-safety.com

[bolle-safety.com](http://bolle-safety.com)

U.K. Bollé Safety  
Unit C83 - Barwell Business Park Leatherhead Road - Chessington  
Surrey - KT9 2NY  
Tél. : 00 44 (0)208 391 4700  
Fax : 00 44 (0)208 391 4733  
e-mail : sales@bolle-safety.co.uk

**bolle**  
SAFETY