# STREAM EVO™



Stream Evo safety glasses provide extreme comfort and 'wearability' with a range of lens options to suit a variety of conditions.

# **SPECIAL FEATURES**

- Single wraparound polycarbonate lens
- Soft, ventilated TempFLEXTM temple tips provide a comfortable, secure fit
- Slim temples enhance comfort when worn with ear defenders
- Lateral protection
- 100% metal free
- Soft, adjustable, anti-slip nose bridge
- Stream Evo Accessory Pack available separately. Contains adjustable headband and gasket.















VERSIONS	REF.	LENS MARKING	FRAME MARKING	PROTECTION AGAINST	COATINGS
CLEAR	RLY00361	2C-1.2 € 1FTKN C €	<b>e</b> 'EN 166 FT <b>C €</b>	Impacts, UV radiations	TECTON 400 K&N Anti-scratch and Anti-fog / UV400 / Moisture repellent
GREY	RLY00362	5-2.5 <b>€</b> 1FTKN <b>C €</b>	<b>€</b> 'EN 166 FT <b>C €</b>	Impacts, UV and Solar radiations	/ UV400 / Moisture repellent
ANTI-REFLECTIVE	RLY00363	5-1.7 <b>€</b> 1FT <b>C</b> €	<b>e</b> 'EN 166 FT <b>C €</b>	Impacts, UV radiations	
TWILIGHT	RLY00364	5-1.7 <b>€</b> 1FT <b>C</b> €	€ EN 166 FT C €	Impacts, UV radiations	
ACCESSORY PACK	RLYA0017	N/A	N/A	N/A	N/A

See overleaf for this product's technical specification ....>



# STREAM EVO™



#### **GENERAL SPECIFICATION**

LENS BASE	9.5mm
WEIGHT	23g

#### **PACKAGING**

Individually contained in a polythene bag with a Euroslot

PER BOX	10
PER CARTON	200

#### **COMPONENT SPECIFICATION**

COMPONENT	MATERIAL	FEATURES	
<b>LENS</b> Polycarbonate		One piece moulded lens with side protection	
NOSE BRIDGE	Thermoplastic Elastomers (TPE)	Comfortable and flexible	
TEMPLE	TR90 Thermoplastic / Thermoplastic Elastomers (TPE)	Co-injected - Robust, flexible, lightweight and ventilated	
HINGE	TR90 Thermoplastic	Metal free and durable	

#### **LENS MARKINGS**

#### LENS FILTER TYPE:

2C UV

5 Solar

#### SCALE NUMBER (SHADE):

1.2 Clear or Amber

1.7 Minimises or I/O

2.5 Grey or Revo

@ Identity of manufacturer

#### **OPTICAL CLASS:**

High optical quality

#### MECHANICAL STRENGTH:

F Low energy impact, resists a 6mm, 0.86g ball at 45m/s

T Protection against high-speed particles at extreme temperatures

#### PERFORMANCE:

K Resistance to scratches by fine particles

N Resistance to fogging

C€ Certification mark

#### **FRAME MARKINGS**

@ Identity of manufacturer

**EN 166:** guaranteed minimum resistance of the protective eyewear against everyday risks including dropping the protective eyewear onto the ground, ageing by light exposure, exposure to heat or corrosion etc.

# MECHANICAL STRENGTH:

F Low energy impact, resists a 6mm, 0.86 g ball at 45m/s

T Protection against high-speed particles at extreme temperatures

C€ Certification mark

### **CLEANING AND STORAGE**

**CLEANING:** The lenses should be cleaned regularly.

MAINTENANCE: Pitted, scratched or damaged lenses must be replaced by replacing the complete product. If the frame is damaged also replace the

complete product. After each use it is recommended to keep the spectacles or goggles in a microfibre pouch or rigid case.

STORAGE: All products must be stored in a dry and clean environment.

# PART OF THE GLOBUS GROUP

Based on a substantial heritage of successfully protecting hands, Globus has grown to become one of the world leaders in worker safety, leading the way in technical innovation to provide a range of products that have set the standard for safety, productivity and wearer acceptance.

This focus on creating cutting edge personal protection solutions has now extended to eye and face protection with Riley; a new collection of high performance protective eyewear products engineered with innovation and ingenuity, designed for optimum comfort and styled for safe working.

Riley product approval certificates to CE standards will be provided on request. Riley is a registered trademark.

# www.riley-eyewear.com

E: info@riley-eyewear.com

T: +44 (0)161 877 4747

F: +44( 0)161 877 4746

Globus (Shetland) Ltd, 14 Central Park, Mosley Road, Manchester, M17 1NY, UNITED KINGDOM

