

Product Datasheet model skyguard NT 9175 260



UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth

<p>Product characteristics</p>	<ul style="list-style-type: none"> * An improved spectacle with all-round protection * An injection moulded TPU frame increase wearer protection levels through minimising the risk of particle ingress * The flexible, closed-pore soft components enables a customised, individual fit * Easy to clean to promote long term use * Comfortable, customized fit by individual side arm inclination and length adjustment
<p>Technical details</p> <p>Frame</p> <p>Material</p> <p>Colour</p> <p>Material</p> <p>Colour</p>	<p>Front piece</p> <p>PP</p> <p>blue</p> <p>TPU layer</p> <p>TPU</p> <p>grey</p>

Material	Side piece
Features	PBT+PC
Colour	adjustable inclination
	blue
	Temple
Material	PP
Features	adjustable to four different lengths
Colour	blue
Lens	
Material	PC
Thickness	2,1 mm
Filter	2-1,2 according to DIN EN 170
Coating	supravision HC-AF
Colour	clear
Optical class	1
Impact resistance	F (45 m/s) according to DIN EN 166
Miscellaneous	
Weight	42 g
Packing	5 spectacles
	160 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 170