

Product Datasheet model super f OTG 9169 543



UVEX ARBEITSSCHUTZ GMBH, Würzburger Str. 181-189, D-90766 Fürth

<p>Product characteristics</p>	<ul style="list-style-type: none"> * Lightweight cover spectacle with hinge and unrestricted lateral vision * Protective covering thanks to flat base curve * Lens inclination of 11° ensures good view downwards and provides the wearer safeness from stumble-accidents * x-stream-technology (XST) – flexible temple concept that adjusts to different wearing situations, with or without prescription glasses
<p>Technical details</p> <p>Frame</p> <p>Material</p> <p>Features</p> <p>Colour</p> <p>Manufacturer's ID code</p> <p>Applicable EN norm</p> <p>Low-energy impact</p> <p>Conformity symbol</p>	<p>Front piece/Temple</p> <p>PA/TPU</p> <p>XST-temple</p> <p>black/green</p> <p>Marking</p> <p>W</p> <p>166</p> <p>F (45 m/s)</p> <p>CE</p>

Lens	
Material	PC
Thickness	2,1 mm
Coating	infradur PLUS
Colour	grey
	Marking
Filter	shade 3 according to DIN EN 169
Manufacturer's ID code	W
Optical class	1
Low-energy impact	F (45 m/s)
Resistance to high speed particles at extremes of temperat.	T
Surface resistance to fine particles	K
Conformity symbol	CE
Miscellaneous	
Weight	38 g
Packing	5 spectacles per box 160 spectacles per cardboard box
Standards	DIN EN 166 + DIN EN 169