Technical Data Sheet	Title: 0800Water	
Effective Date: Nov 2017	Prepared By: Sam Murphy	
Issue Number: 3	Authorised By: Robin Lamb	



Product Description

Water grade PTFE thread seal tape. (Polytetrafluoroethylene 100% Raw Polymer)

Applications

Commonly used in the plumbing & heating industries for sealing pipe threads such as Water and Propylene Glycol, Kerosene and Diesel.

Features & Benefits

Non-adhesive no need for messy compounds Won't harden or dry out Air & watertight seal Impermeable to >7bar Resistant to cracking Performs a lubricating function

Technical Performance

Description	Units	Value
Tape thickness	mm	0.076 ±10%
Temperature	°C	-60 to +260
Density	gr/cm3	0.33
Pressure	Bar	7

Declaration of Conformity Information

BS 7786:2006 Grade L EN-751-3:1997 DIN30660 WRAS Approval 1804504 re-approval of 1306504 Methane Screwed Fittings up to 300Bar pressure Sulphuric Acid 30%

REACH SVHC Status – NO SHVC present according to candidates list of 17th Dec 2015

RoHS Compliance Status - Yes

Storage Details

Shelf life indefinite stored at the moderate temperature and humidity environment.

The information supplied is accurate to the best of Bruce Douglas Marketing's knowledge and is based upon all current data available to it. Properties quoted are typical and do not therefore constitute a specification. Customers must complete their own assessment of the product for its intended application under their own conditions. Our technical advice is to be regarded as an expression of opinion only and although such advice is given in good faith, it shall not, in any circumstances, be regarded as the basis of or as being a representation or statement of fact. This applies also where propriety or protective rights of third parties are involved. Any liability arising in respect of our products will be strictly limited to the value of those products charged to the customer and shall not extend to any consequential loss whatsoever and howsoever arising. This document does not form part of any contract with a customer (02/05/13)