



Tork Premium Multipurpose Cloth 520 Grey Roll



article: 520304

system: W1 - Wipers wall/floor/standard system

Layers: 1

Colour: Grey

Print: no

Embossing:

Roll Width: 42.8 cm

Roll Length: 361 m

Number of Sheets: 950

Sheet Length: 38 cm

Roll Diameter: 38 cm

product properties

Soft and with a textile feeling

Softness makes it flexible and enables cleaning in tight corners

The soft material is gentle to the surface to prevent scratches

Can be used with most kind of solvents for a clean surface.

shipping data

consumer unit:

EAN: 7322540057461

pieces: 1

height: 437 mm

width: 391 mm

length: 391 mm

volume: 66.8 dm³

net weight: 10043 g

gross weight: 10905 g

transport unit:

EAN: 7322540057478

pieces: 1

consumer units: 1

material: Carton

height: 437 mm

width: 391 mm

length: 391 mm

volume: 66.8 dm³

net weight: 10.04 kg

gross weight: 10.85 kg

environmental

Content

Chemical pulp, Polypropene, Polyester, Chemicals

Material



Chemical pulpChemical pulp is produced either from softwood or hardwood. The wood chips are boiled together with chemicals and the major part of the lignin is removed. Chemical pulp is bleached in order to achieve a clean, bright and strong product, but also to increase the hygienic and absorbent qualities. There are two major bleaching methods: ECF (elementary chlorine free) and TCF (totally chlorine free). ECF is based on oxygen, chlorine dioxide and hydrogen peroxide. TCF is based on hydrogen peroxide and ozone. ECF is used in this product.

PolypropenePolypropene fibre is produced from polypropene resin. The resin is melted in an extruder and spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibre length. **Polyester**Polyester fibre is produced from terephthalic acid and ethyleneglycol, which react through condensation to polyester resin. The molten resin is spun to fibres through spinnerettes and cooled with air. Fibres are then cut to intended fibre length. The fibre used contains black pigments. **Chemicals** Both functional and process chemicals are used. The functional chemical used is wet strength agent. The wet strength agent is a polyamide (from polyamide/epichlorhydrine polymer) with a very high affinity to the fibre. Process chemical used is a surfactant.

Production

This product is produced at Suameer mill, The Netherlands, and certified according to ISO 9001:2000, ISO 14001 and EMAS.

Destruction

This product is mainly used for industrial processes and hence it will be contaminated with different substances. This will determine how the used product will be destroyed. The product itself is suitable for incineration. Contact local authorities before destruction.