



PRODUCT DATA SHEET

AF4R WORK Area Floodlight (2000)



AF4R Work

PRODUCT DESCRIPTION

The Ledlenser AF4R Work area floodlight is compact and bright – our smallest Hybrid Power floodlight, a versatile all-rounder. Whether illuminating a fuse box, or brightening up worksites, this light is a perfect companion. Painters, electricians, engineers, and DIY enthusiasts alike will find everything they need in the AF4R Work.

- Compact yet powerful floodlight with up to 2000 lm, 5 Brightness levels and 5-step tunable white light
- Efficient directed light, maximum illuminance and reduced glaring thanks to Multi-Concentrated Light technology
- HyErid Power; powerful rechargeable battery as well as mains operation
- High water and dust protection (IP67), robust aluminum housing and flexible mounting
- Bluetooth ready⁶, separately available Controller for Area Lights
- 7-year with registration warranty for complete peace of mind

TECHNICAL DATA

Width [mm]	266
Depth [mm]	44
Height [mm]	119
Weight incl. batteries [g]	1370
Weight without batteries [g]	1220
Focus function	No
Primary material	Aluminum alloy
Secondary material	Other plastics
Optic	Reflector
Cartridge	No

POWER SUPPLY

Power source type	Rechargeable battery
Battery quantity	1
Battery type	Li-ion
Battery replaceable	No
Total battery voltage [V]	7.2
Total battery capacity [mAh]	4700
Total battery energy ² [Wh]	33.84
Rechargeable	Yes
Charging time ⁵ [min]	360
Energy modes	Constant Light
Energy status indicator	Runtime indicator, Battery Indicator, Charge Indicator, Low Battery Warning

FURTHER SPECIFICATIONS

IP class	IP67
Drop test (drop height) [m]	1.5
IK Code [J]	7
Working temperature range [°C]	-20 to +40

LIGHT FUNCTIONS

Low Power, Mid Power, Power

LIGHT SOURCE

Main

Colour	Tunable white
Colour temperature [K]	3000 to 6500
Colour rendering index (CRI)	80

LIGHT VALUES

ANSI – Constant Light	Power	Mid Power	Low Power
Light output ¹ [lm]	2000	1000	200
Beam distance ¹ [m]	60	50	20
Run time ¹ [h]	2	4	20

SWITCH

Multifunctional Switch

FEATURES

Tunable white, Reduced Peripheral Glare, Transportation lock, Dimmable, Memory function

TECHNOLOGIES

Multi-Concentrated Light, Hybrid Power, Temperature Control System, Cooling Technology

AF4R Work

PACKAGING AND LOGISTICS



PACKAGING INFORMATION

Type of packaging	Sleeve Case
Supplied with	Power adapter, USB cable Diffuser
Item No.	502910
Customs tariff number	94054099900
Colour	black

SINGLE PACKAGE

Dimensions W x H x D [cm]	45.5 x 9.6 x 30.3
Gross weight [g]	3660
GTIN-13	4058205033053

EXPORT CARTON

Unit	2
Dimensions W x D x H [cm]	48 x 21.5 x 35.5
Gross weight [kg]	7.9
GTIN-13	4058205033039

AF4R Work

ACCESSORIES

ITEM NUMBER	PRODUCT NAME
503016	Extension Cable 5m
503018	Controller for Area Lights

FOOTNOTES

The information pertaining to scope of delivery, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change scope of delivery, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and omissions excepted.

1) Measurement values according to ANSI FL1 in the respective setting. If no setting is explicitly indicated, the values refer to luminous flux (lumens/lm) and lighting range (meters/m) on the highest setting, and to battery duration (hours/h) on the lowest setting. A boost function (if available) can be used several times, but only for short periods of time. If the light is equipped with (a) colored LED(s), the measurement values are given for the white light or the white LED. If the light has different energy modes, the measurement is made based on the "energy saving mode".

2) Calculated capacity value in watt-hours (Wh). This applies to the delivery state of the battery/ies inside the respective item, or for lights with rechargeable battery/ies, to the rechargeable battery/ies inside the product when fully charged.

5) Charging time varies by hardware used.