



— PRODUCT DATA SHEET
P3R



P3R



PRODUCT DESCRIPTION

Trusted to deliver exceptional lighting performance for its size, the P3R key-ring torch features the tried-and-tested Advanced Focus System for easy Spot/Flood focusing that creates the optimal light pattern for any range. It operates with either rechargeable or disposable batteries. Additionally, the P3R is friendlier on the environment as all aluminium components are made of 75 % recycled material. Backed by a 7-year with registration warranty for complete peace of mind.

- Rechargeable key-ring torch with Spot/Flood focusing function (Advanced Focus System) and three brightness levels
- Dual Power Source: Operates with rechargeable and disposable batteries, charging via USB-C port on battery (charging cable not included)
- Intuitive operation via End Cap Switch
- Sustainable: Use of 75 % recycled aluminium⁹ and backed by a 7-year warranty*
- Keyring to safely attach the torch to keys or backpack

TECHNICAL DATA

| | |
|----------------------------|----------------|
| Weight incl. batteries [g] | 41 |
| Material | Aluminum alloy |
| Length [mm] | 94 |
| Length (focused) [mm] | 98 |
| Tube diameter [mm] | 15 |
| Head diameter [mm] | 20 |

POWER SUPPLY

| | |
|------------------------------|---------------------------------|
| Battery quantity | 1 |
| Rechargeable | Yes |
| Battery type | Lithium-ion |
| Total battery voltage [V] | 3.7 |
| Total battery capacity [mAh] | 300 |
| Total battery energy [Wh] | 1.11 Wh |
| Battery replaceable | Yes |
| Charging time [min] | 90 |
| Useable batteries | Micro (AAA) 1.5V, AAA NiMH 1.2V |

FURTHER SPECIFICATIONS

| | |
|--------------------------------|------------|
| IP class | IP54 |
| Drop test (drop height) [m] | 2 |
| Working temperature range [°C] | -20 to +40 |

LIGHT FUNCTIONS

Cool White Main: Power, Mid power, Low power

LIGHT SOURCE

| | MAIN |
|------------------------------|--------------|
| Amount LEDs | 1 |
| Colour | Cool White |
| Colour temperature [K] | 6000 to 7500 |
| Colour rendering index (CRI) | 70 |

LIGHT VALUES - Cool White Main

| | Power | Mid power | Low power |
|-------------------|-------|-----------|-----------|
| Light output [lm] | 200 | 80 | 20 |
| Beam distance [m] | 130 | 80 | 40 |
| Run time [h] | 1.5 | 2.5 | 8 |

SWITCH

End-cap Switch

TECHNOLOGIES

Advanced Focus System, Dual Power Source, Rapid Focus

P3R

PACKAGING AND LOGISTICS



For illustration purposes only

PACKAGING INFORMATION

| | |
|----------------------------------|--|
| Type of packaging | Box |
| Supplied with | Key ring, 10440 Li-ion USB-C direct charging battery |
| Item No. | 503107 |
| Colour | Black |
| STERLING RRP inc / ex vat | £46.95 / £39.13 |
| EURO RRP inc / ex vat | €TBC / €TBC |

SINGLE PACKAGE

| | |
|---------------------------|------------------|
| Dimensions W x H x D [cm] | 14.5 x 8.5 x 4.2 |
| Gross weight [g] | 94.5 |
| GTIN-13 | 4058205037259 |

EXPORT CARTON

| | |
|---------------------------|----------------|
| Unit | 24 |
| Dimensions W x H x D [cm] | 37.5 x 17 x 31 |
| Gross weight [g] | 2930 |
| GTIN-13 | 4058205037235 |

— P3R

PRODUCT SERIES

Powerful torches for those who push boundaries—the discerning enthusiasts, the industrious workers, the bold adventurers and the forward-thinkers. Lights that bridge the gap between the epic and the technical. In your hand, they do more than shine—they guide your path, reveal the unknown and empower you to explore, discover and redefine what is possible. Pioneering Brilliance. The P-Series: Redefined.

— P3R

FOOTNOTES

The information pertaining to scope of delivery, appearance, performance, dimensions and weight corresponds to the information available at the time of publication. In the interest of product development, we reserve the right to change scope of delivery, appearance, design and color without prior notice. Product images may vary from the actual products and may show optional accessories which can be purchased separately. Errors and omissions excepted.

*) 7 year warranty only if registered, otherwise 2 years. Warranty conditions viewable at <https://ledlenser.com/en/infos-service/warranty/>

1) Measured values according to ANSI/PLATO FL 1 in the respective setting named. If no setting is specifically named, the luminous flux (lumens/lm) and range (meters/m) values refer to the brightest setting and the burn time

(hours/h) values refer to the lowest setting. A boost function (if available) can be used several times, but is only available for a short time at a time. In case the lamp is equipped with colored LED(s), the measured values are given with white light or the white LED. If the lamp has different energy modes, the "energy saving mode" is the basis for the measurement.

2) Calculated value of the capacity in watt-hours (Wh). This applies to the battery(ies) contained in the delivery condition of the respective item or, in the case of lamps with rechargeable battery, to the battery(ies) contained herein in a fully charged condition.

9) All aluminium components are made of at least 75 % recycled aluminium and may thus vary in surface structure and color.