

Medium Duty Green PVC S&D Hose

Specification Sheet

Product Code: 5302---

For further information:

Arco Ltd, PO Box 21, Waverley Street, Hull, HU1 2SJ

hose@arco.co.uk

www.arco.co.uk

Tel: 01482 383280

Fax: 01482 591450



A PVC hose, reinforced with a rigid shock-proof white PVC helix, suitable for multi-sector applications.

Construction: Hose wall – green PVC
Helix – white shock-proof PVC

Applications: Suction and delivery of water, slurries and powders
Agricultural, horticultural, marine and construction industries

Properties: Flexible and economical
Optimum flow is maintained by the smooth bore
Not suitable for hydrocarbons
Resistant to chemicals (please check chemical compatibility)
Phthalate free materials

Temperature range: -15°C to +60°C

Standard length: 30 metres

I.D. (mm)	O.D. (mm)	Working Pressure (bar)	(psi)	Bend Radius (mm)	Vacuum (mmHg)	Weight (kg/m)	Code
25	31.8	5	72	60	525	0.36	5302025
32	39.0	5	72	75	450	0.46	5302032
38	45.4	5	72	90	450	0.57	5302038
51	59.6	5	72	95	450	0.83	5302051
63	71.8	5	72	115	375	1.05	5302063
76	86.6	5	72	120	375	1.47	5302076
102	114.6	3	43	180	375	2.17	5302102
152	166.4	3	43	320	375	4.22	5302152

All pressure ratings quoted at ambient temperature