

Light Duty Green Tint PVC

S&D Hose

Specification Sheet

Product Code: 5303---

For further information:

Arco Ltd, PO Box 21, Waverley Street, Hull, HU1 2SJ

hose@arco.co.uk

Tel: 01482 383280

www.arco.co.uk

Fax: 01482 591450



A lightweight PVC hose, reinforced with a rigid crush resistant white PVC helix, suitable for multi-sector applications.

Construction: Hose wall – transparent green PVC
Helix – white crush resistant PVC

Applications: Delivery and light duty suction of water, slurries and powders
Agricultural, horticultural, marine and construction industries
Suitable for conveying liquid fertilisers, dilute chemicals and insecticides

Properties: Tough, flexible and extremely durable
Optimum flow is maintained by the smooth bore
Translucent wall aids in locating blockages
Outstanding resistance to the effects of weather

Temperature range: -10°C to +55°C

Standard length: 30 metres

I.D. (mm)	O.D. (mm)	Working Pressure (bar)	(psi)	Bend Radius (mm)	Vacuum (mmHg)	Weight (kg/m)	Code
19	24.6	9	131	86	514	0.28	5303019
25.4	32	8	116	114	514	0.33	5303025
32	39.2	7	102	143	514	0.46	5303032
38	45.4	6.5	94.3	171	514	0.55	5303038
51.6	59.8	6	87	230	514	0.81	5303051
63.5	71.9	5	72.5	284	514	1.04	5303063

All pressure ratings quoted at ambient temperature