

Mobile Safety Step (Anti-slip)



Specifications

Brand: TB DaviesWarranty: 1-yearMax Load: 150kg

- Standard: BS EN 131-7:2013

- Material: Steel

Commodity Code: 73269030Country of Origin: GBRecommended Usage: Intensive

- Recommended Osage, Intensive

Common Dimensions

- Rung Depth: 180mm

- Distance Between Rungs: 210mm

- Handrail Height: 950mm

Availability & Delivery

Non-stock item. Delivery Up To 21 Days. (See exceptions, if applicable, overleaf)

[Representative image of product]

Product Description

Kitemarked and tested by BSI to EN131-7, these steps are constructed from strong tubular mild steel with double handrail, toe-boarded platform and enclosed guardrail for assured working and stock picking in commercial environments. Available in a range of sizes with an anti-slip mat fitted to the tread and top platform step for maximum grip. Fully compliant to EN131-7.

Features

- Large 560 x 400mm top platform tread to comfortably work from
- Locking device and anti-ascent bar
- Please Note, 10 tread & above supplied in 2 parts
- Easy one user manoeuvrability on 4 x rolling wheels
- Optional extras available for full customisation
- Not suitable for outdoor use

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed.

This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.



Mobile Safety Step (Anti-slip)

Product Dimensions

SKU	Treads	Platform Height	Approx. Working Height ¹ (mm)	Height (mm)	Width (mm)	Depth (mm)	Nett Weight (kg)
2018-004	4	1000	2600	2000	905	965	32.0
2018-005	5	1250	2850	2250	950	1120	55.0
2018-006	6	1500	3100	2500	995	1275	62.0
2018-007	7	1750	3350	2750	1040	1430	70.0
2018-008	8	2000	3600	3000	1085	1585	78.0
2018-009	9	2250	3850	3250	1130	1740	90.0
2018-010	10	2500	4100	3500	1175	1895	98.0
2018-011	11	2750	4350	3750	1220	2050	106.0
2018-012	12	3000	4600	4000	1265	2205	116.0
2018-013	13	3250	4850	4250	1310	2360	122.0
2018-014	14	3500	5100	4500	1355	2515	130.0
2018-015	15	3750	5350	4750	1400	2670	138.0

¹ Working height is calculated as 1,600mm plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of 75° degrees. Note that 10 tread and above are supplied in 2 sections, which require bolting together before first use.

Shipping Dimensions

SKU	Barcode	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m³)	Gross Weight (kg)
2018-004	5060169481183	2000	965	905	1.747	32.0
2018-005	5060169481190	2250	1120	950	2.394	55.0
2018-006	5060169481206	2500	1275	995	3.172	62.0
2018-007	5060169481213	2750	1430	1040	4.09	70.0
2018-008	5060169481220	3000	1585	1085	5.159	78.0
2018-009	5060169481237	3250	1740	1130	6.39	90.0
2018-010	5060169481244	3500	1895	1175	7.793	98.0
2018-011	5060169481251	3750	2050	1220	9.379	106.0
2018-012	5060169481268	4000	2205	1265	11.157	116.0
2018-013	5060169481275	4250	2360	1310	13.139	122.0
2018-014	5060169481282	4500	2515	1355	15.335	130.0
2018-015	5060169481299	4750	2670	1400	17.756	138.0

Please note that products marked 'Special Order' cannot be cancelled and are non-returnable once orders are acknowledged and placed.

This document is presented as a guide only; It is subject to change without notice and as such is not legally binding, nor does it form part of any contract.