

Stepmobile



Common Dimensions

Tread Width (mm)	380
Tread Depth (mm)	180

Product Dimensions

* 2 Tread comes without a handrail

PRODUCT SKU	APPROX. WORKING HEIGHT* (M)	PLATFORM HEIGHT (M)	TREAD COUNT	PLATFORM SIZE (MM)	OVERALL HEIGHT (M)	OVERALL WIDTH (M)	OVERALL DEPTH (M)	WEIGHT (NETT KG)
2010-001	2.1	0.5	2	380 x 180	0.6	0.5	0.5	10.0
2010-002	2.1	0.5	2	380 x 280	1.2	0.6	0.5	12.0
2010-003	2.4	0.8	3	380 x 280	1.4	0.6	0.8	14.0
2010-004	2.6	1.0	4	380 x 280	1.7	0.6	1.0	17.0
2010-005	2.9	1.3	5	380 x 280	1.9	0.6	1.1	20.0

»*Working height is calculated as 1,600mm plus the height of the platform or last climbing tread, whichever is appropriate.

»Tread count includes top platform step



Technical Description

Steel narrow aisle step, widely used in office, library and archiving environments. Strong sprung castors lock and hold in place when weight is applied. The zero turning circle makes them easy to manoeuvre in tight spaces. Long double handrails and a guard railed top tread provide extra assurance for users.

- » Spring loaded swivel castors retract when weight is applied
- » Dome covers have high grip rubber wrap-around bumpers
- » Effortless manoeuvrability
- » Safe 280mm deep anti-slip ribbed rubber treads
- » Platform size 280 x 380mm
- » Continuous hand and guardrail for safety
- » Robust tubular steel construction
- » Hard wearing powder coated finish in a choice of colours
- » ***Not suitable for outdoor use*** - see galvanised option below

Standards & Classification

- » Max Load 150kg

Warranty

- » 1 Year

Commodity Code

- » 73269030

Shipping Dimensions

PRODUCT SKU	SHIPPING LENGTH (HEIGHT) (MM)	SHIPPING WIDTH (MM)	SHIPPING DEPTH (MM)	SHIPPING VOLUME (M ³)	SHIPPING WEIGHT (GROSS KG)	BARCODE
2010-001	600	500	500	0.1746	10.0	5060169483279
2010-002	1,200	600	500	0.3711	12.0	5060169483286
2010-003	1,400	600	800	0.6571	14.0	5060169483293
2010-004	1,700	600	1,000	0.9322	17.0	5060169483309
2010-005	1,900	600	1,100	1.2602	20.0	5060169483316

Additional Options

- » Product can be supplied as galvanised

Please call our sales team to discuss these options*