

Truck Dock Platform Steps



[Representative image of product]

Product Description

A fully welded, heavy-duty platform step constructed from box section mild-steel. The 48 degree slope enables users to ascend or descend facing forwards and the large top platform tread enables a safe, comfortable working area. Fitted with 3 x chain guardrails to enable easy access to machinery, vehicles or storage areas. Heavy-duty castors enable the Truck Dock Platform to be easily wheeled into position.

Features

- Large platform with removable chain on end and both sides for 3-sided access
- Comfortable 750mm wide treads
- 48-degree shallow slope for extra safety
- Easy one user manoeuvrability on 4 x rolling wheels
- Optional extras available for full customisation
- Platform size 750 x 1200mm

Specifications

- Brand: TB Davies
- Warranty: 1-year
- Material: Steel
- Commodity Code: 73269030
- Country of Origin: GB
- Recommended Usage: Intensive

Common Dimensions

- Rung Depth: 180mm
- Distance Between Rungs: 210mm
- Handrail Height: 0mm

Availability & Delivery

Non-stock item. Delivery up to 21 days.
(See exceptions, if applicable, overleaf)

Truck Dock Platform Steps

Product Dimensions

SKU	Treads	Platform Height	Approx. Working Height ¹ (mm)	Height (mm)	Width (mm)	Depth (mm)	Nett Weight (kg)
2024-003	3	690	2290	1680	960	1680	80.0
2024-004	4	920	2520	1910	960	1870	89.0
2024-005	5	1150	2750	2140	960	2060	98.0
2024-006	6	1380	2980	2370	960	2250	107.0
2024-007	7	1610	3210	2600	960	2440	116.0
2024-008	8	1840	3440	2830	960	2630	125.0

¹ Working height is calculated as 1,600mm plus platform height or last climbing tread, whichever is appropriate. Ladders set at an angle of 75° degrees.
Note that 10 tread and above are supplied in 2 sections, which require bolting together before first use.

Shipping Dimensions

SKU	Barcode	Shipping Length (mm)	Shipping Width (mm)	Shipping Depth (mm)	Shipping Volume (m³)	Gross Weight (kg)
2024-003	5060169489325	1680	960	1680	2.71	80.0
2024-004	5060169481572	1910	960	1870	3.429	89.0
2024-005	5060169481589	2140	960	2060	4.232	98.0
2024-006	5060169481596	2370	960	2250	5.119	107.0
2024-007	5060169481602	2600	960	2440	6.09	116.0
2024-008	5060169481619	2830	960	2630	7.145	125.0