
COBAMAT LIGHT

KEY FEATURES

- Reduces operator leg and backache.
- Insulates the operator from a cold concrete floor.
- Cross-ribbed surface provides extra grip.
- Helps to keep work areas clean as debris falls through the holes and can be swept away with ease.
- O Cost effective -cheapest in the Cobamat Range



SUITABLE APPLICATIONS

♦Wet/Oily and Dry environments.

FATIGUE PREVENTION	WEAR TOLERANCE	SLIP RESISTANCE
Moderate	Good	Good

PRODUCT DATA

Material: Flexible PVC extrusions
Appearance: Cross-ribbed woven

Hole size 30 mm x 30 mm, thickness 12 mm

industrial chemicals.

UV Resistance: Resistant to UV - NB>Red is not colourfast in direct

sunlight.

Operating Temperature: -20°c to +60°c

Flame Retardancy: Conforms to DIN 4102

INSTALLATION & CLEANING

Installation: Simply unrolled or laid loose

Cleaning: Pressure wash or steam clean using, if required, a

mild detergent.

SIZES & OPTIONS

Optional Extras: * Bevelled Safety Edging factory fitted to help keep

the matting in

place and to prevent operators tripping onto the

mat.

Sizes: Available in rolls or single mats.

Widths: 0.6 m, 0.9 m, 1.0 m, 1.2 m and 1.5

m

Lengths: 5 m or 10 m

Special sizes available on request

Colours: Red, Black, Blue, Green, Yellow, Grey or Brown

Country of Origin: UK

* Please refer to Support Notes at back of Manual