



Solid Fatigue-Step

Modular anti-fatigue matting for larger areas



- Tiles link together to provide a very comfortable anti-fatigue surface.
- Simple to press-together connectors for installation on-site.
- Compatible with Fatigue-Step Grit tiles.
- Can withstand temperatures of up to 160°C and spillage of molten glass.
- Individual tiles can be moved and replaced with ease.
- Manufactured with Natural rubber and 25% nitrile.
- Fully slip tested – see datasheet for details.
- Optional ramped edging in yellow or black.



Parts

Part Number	Size	Colour	Weight (kg)
ST010001	0.9 m x 0.9 m	Black	10.5

Technical Specifications

Material	Standard - Natural rubber with 25% NBR.
Surface Finish	Solid textured
Product Height	18 mm
Min. Operating Temperature	-20°C
Max.	+130°C

Operating Temperature	
Resistance to Chemicals	Limited resistance to chemicals and oils
Environmental Resistance	Suitable for wet and dry environments. Will withstand welding splatter and spillages of other hot materials.
UV Resistance	Yes
Typical Applications	General industrial
Installation Method	Loose lay interlocking tiles
Accessories	SS00#1, SSNB#1, ALUR#1
Cleaning Method	Use of hard detergents not recommended
Storage and application	Store at room temperature, free from deformations.
Tensile Strength	3.5 to 4 MPa
Notes	Silicone is used in the production process of the mats and a residue will possibly be left on the mat. This can be washed off using hot soapy water
Slip Tested to	DIN 51130 - R10

Additional Information



Installation Guide



Solid Fatigue Step Ramp Slip Test DIN 51130

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@coba.com

www.coba.com