




## Entra-Plush

Plush carpet doormat with crush resistance


- Crush-resistant and quick-drying plush carpet surface.
- Ideal for wiping moisture from wet footwear.
- Carpet fibres effectively scrape and trap dirt at the point of entry.
- Slip and stain-resistant PVC backing keeps the mat in place.
- Ideal for commercial environments, such as offices.



## Styles Available



Red



Grey



Brown



Blue

# Parts

| Part Number | Size          | Colour | Weight (kg) |
|-------------|---------------|--------|-------------|
| PP060003    | 1.2 m x 1.8 m | Grey   | 5.85        |
| PP050003    | 1.2 m x 1.8 m | Brown  | 5.85        |
| PP030003    | 1.2 m x 1.8 m | Red    | 5.85        |
| PP020003    | 1.2 m x 1.8 m | Blue   | 5.85        |
| PP060002    | 0.9 m x 1.5 m | Grey   | 3.55        |
| PP050002    | 0.9 m x 1.5 m | Brown  | 3.55        |
| PP030002    | 0.9 m x 1.5 m | Red    | 3.55        |
| PP020002    | 0.9 m x 1.5 m | Blue   | 3.55        |
| PP060001    | 0.6 m x 0.9 m | Grey   | 1.45        |
| PP050001    | 0.6 m x 0.9 m | Brown  | 1.45        |
| PP030001    | 0.6 m x 0.9 m | Red    | 1.45        |
| PP020001    | 0.6 m x 0.9 m | Blue   | 1.45        |

# Technical Specifications

|                          |                                       |
|--------------------------|---------------------------------------|
| Material                 | PP                                    |
| Backing                  | PVC                                   |
| Surface Finish           | Cutpile                               |
| Product Height           | 7 mm +15% / -10%                      |
| Product Weight           | 2.59 kg / m²                          |
| Pile Height              | 4 mm                                  |
| Pile Yarn Composition    | 100% PP                               |
| Pile Weight              | 0.45 kg / m²                          |
| Environmental Resistance | Suitable for indoor environments only |
| Typical Applications     | Entrance areas                        |
| Installation Method      | Loose lay                             |
| Cleaning Method          | Vacuum top surface                    |

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email [sales@coba.com](mailto:sales@coba.com)

[www.coba.com](http://www.coba.com)