

**PRODUCT DATASHEET**

**Product: BUBBLEMAT**

Standard Mat Size m. Width X Length	Weight Kg.	Packaging Size m.	Package Type	Package Volume m	Package Quantit y	Colours
0.6 X 0.9		0.8 X 0.19 X 0.19	Box	0.029	1	Black
0.9 x 1.2		0.97 X 0.19 X 0.19	Box	0.035	1	Black
0.6 X 0.9 end		0.8 X 0.19 X 0.19	Box	0.029	1	Black
0.6 X 0.9 middle		0.8 X 0.19 X 0.19	Box	0.029	1	Black

**Material:** Natural rubber  
**Surface Finish:** Bubble shaped  
**Product Height:** 18 mm nominal

**Operating Temperature:** - 20<sup>0</sup> - + 160<sup>0</sup>

**Resistance to Chemicals:** Resistant to water and most mild acids  
**Environmental Resistance:** Use predominantly in dry areas.  
**UV Resistance:** N/A

**Typical Applications:** Ideal for manufacturing production areas where employees are standing in static positions. Bubble surface constantly stimulates blood circulation to reduce fatigue  
**Installation Method:** Individual components that lock together to cover any desired length or individual mats complete with bevel edge all round

**Cleaning method:** Hose down or pressure wash using a mild detergent.  
**Product Performance:**

<b>Fatigue:</b>	●●●●
<b>Slip Resistance:</b>	●●
<b>Wear:</b>	●●●
<b>Low → High</b>	● → ●●●●

**Flame Retardancy:** N/A

**Country of Origin:** INDONESIA

The information contained within this datasheet is for guidance only. The data and suggested applications included are not exhaustive. All dimensions quoted are nominal figures.

**PLEASE NOTE THAT MATTING PRODUCTS MAY BE SUBJECT TO A DEGREE OF SHRINKAGE WHEN INSTALLED INTO SOME APPLICATIONS.**