



Bubblemat

Smart anti-fatigue mat with a distinctive bubbled surface











- Raised bubble patterned surface stimulates feet and legs to aid circulation.
- Underfoot cushioning also makes prolonged occupational standing more comfortable.
- Complete mats suitable for workstations.



Parts

Part Number	Size	Colour	Weight (kg)
BF010004	0.6 m x 0.9 m	Black	6.35
BF010003	0.6 m x 0.9 m	Black	6.35
BF010002	0.9 m x 1.2 m	Black	10.5
BF010001	0.6 m x 0.9 m	Black	6.35

Technical Specifications

Material	Natural rubber
Recycled Material Content %	43% recycled content
Natural Material Content %	59
Surface Finish	Bubble

Product Height	14 mm	
Min. Operating Temperature	-30°C	
Max. Operating Temperature	+50°C	
Resistance to Chemicals	Not resistant to fat and mineral oil	
Environmental Resistance	Suitable for predominantly dry environments	
UV Resistance	Yes	
Typical Applications	General industrial	
Installation Method	Loose lay interlocking mats	
Cleaning Method	Use a high pressure hose (not exceeding 60psi) to remove the dirt and debris on the mats. For best results use a mild detergent (pH 4.0-9.0) to clean the mats. Do not use steam or degreasers or caustic chemicals. Do not mechanically scrub the mats	
Tensile Strength	3 MPa	
Elongation	250%	
Manufacturing process	Compression moulding	

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@coba.com

www.coba.com