

PRODUCT DATASHEET

Product: POLYPLUSH

Standard Mat Size m. Width X Length	Weight Kg.	Packaging Size m.	Package Type	Package Volume m	Package Quantity	Colours
0.6m x 0.9m		0.8 x 0.19 x 0.19	Box	0.037	1	Grey, Brown, Slate Blue, Green or Red
0.9m x 1.5m		0.97 x 0.19 x 0.19	Box	0.035	1	As above
1.2m x 1.8m						As above

Surface Material: 2950 Denier Continuous Filamant solution dyed Polypropylene Yarn

Backing Material: Specially formulated non staining Vinyl

Operating Temperature: Ambient

Resistance to Chemicals: N/A

Environmental Resistance: Suitable for wet and dry environments. For indoor use only.

Absorbtion: 5.4 litres/square metre

UV Resistance: Yes

Typical Applications: Lobbies, Hallways, Entry areas and doorways.

Installation Method: Loose lay.

Accessories: N/A

Cleaning Method: Vacuum top surface.

Product Performance:

Fatigue:	N/A
Slip Resistance:	•
Wear:	•
Low → High	• → ••••

Flame Retardancy: DOC-FF-1-70

Country of Origin: USA

The information contained within this datasheet is for guidance only. The data and suggested applications included are not exhaustive. All dimensions quoted are nominal figures.

PLEASE NOTE THAT MATTING PRODUCTS MAY BE SUBJECT TO A DEGREE OF SHRINKAGE WHEN INSTALLED INTO SOME APPLICATIONS.