
## ARCO ANTI-FATIGUE RIBBED

## KEY FEATURES

- Cushion effect helps to reduce operator fatigue.
- Ribbed surface minimises slipping.
- An extruded product made from 100% closed cell PVC foam.
- Effectively insulates against a cold concrete floor.
- Widely used on assembly lines in major automotive manufacturing facilities and by second tier suppliers throughout the world.



SUITABLE APPLICATIONS

**♦Dry** environments.

♦ Ideal for INDUSTRIAL use, in dry, indoor situations, particularly PRODUCTION LINES, ASSEMBLY AREAS, PACKING STATIONS and WORKBENCHES.

FATIGUE PREVENTION	WEAR TOLERANCE	SLIP RESISTANCE
Good	Moderate	Moderate

PRODUCT DATA

Material: Virgin Closed Cell PVC (Foam)

Appearance: Ribbed finish

Thickness: 9 mm nominal

Chemical Resistance: \* PVC is resistant to many different chemicals,

alkalis and general

industrial chemicals. Resists alcohol's, aliphatic

hydrocarbons, oils,

weak acids, strong mineral acids and alkalis.

Resists oil and grease if properly cleaned. Does  $\underline{\text{NOT}}$  resist organic solvents, ketones, esters and aromatic

hydrocarbons.

N/A

UV Resistance:

**Operating Temperature:** 0°c to +60°c

Flame Retardancy: Conforms to FMVSS 302. Will not burn after the

ignition source is removed. When 'forced' to burn, Carbon Monoxide, Carbon Dioxide and Hydrogen Chloride

fumes are emitted.

INSTALLATION & CLEANING

Installation:
Loose lay

Cleaning: Brush/mop the top surface.

SIZES & OPTIONS

Sizes: 0.6 m x 0.9 m, 0.9 m x 1.5 m, 0.9 m x 18.3 m

Special sizes available on request.

Colours: Grey/ Charcoal with Yellow Borders

Country of Origin: USA

\* Please refer to Support Notes at back of Manual