



Deckplate Anti-Static

Hardwearing dual layer mat for static sensitive areas



- Hardwearing anti-fatigue mat for static sensitive areas.
- Conductive top surface protects operatives and components.
- Diamond pattern surface is attractive and slip resistant.
- Top surface provides resilience to many industrial chemicals.
- Grounded via a 10 mm male stud fitted to the mat.
- Supplied with ramped edges as standard to reduce the risk of trips.
- Tested to EN14041 resistance requirements.
- Rv: $9.8 \times 10^7 \Omega$



Parts

Part Number	Size	Colour	Weight (kg)
DPS010005C	0.9 m x per linear metre (max. 18.3 m)	Black	8
DPS010005	0.9 m x 18.3 m	Black	108
DPS010915	0.9 m x 1.5 m	Black	8.86
DPS010609	0.6 m x 0.9 m	Black	3.54
DPS010007C	1.2 m x per linear metre (max. 18.3 m)	Black	9
DPS010007	1.2 m x 18.3 m	Black	166

Technical Specifications

Material	Vinyl top surface with PVC foam backing (fusion bonded, not glued)
Surface Finish	Diamond pattern
Product Height	14 mm
Min. Operating Temperature	0°C
Max. Operating Temperature	+60°C
Resistance to Chemicals	The PVC top surface provides limited resistance to chemicals and oils
Environmental Resistance	Suitable for dry indoor environments
Typical Applications	Electronic Industries, electronic components repair shop

Additional Information



Deckplate AS - ESD Test BS EN 14041

Get in touch | To order FREE samples or arrange a site visit please call +44 (0)1788 228 555 or email sales@coba.com

www.coba.com