
PRODUCT DATA SHEET: HERONAIR


SIZES & WEIGHTS

All dimensions are nominal Height (mm) Lengths (m) Widths (cm) Weight (kg/m²)

Tolerances (mm) +/- 0.5 0+0.3 +/- 1

Heronair 10 10 50 75 100 4.5





GENERAL

APPEARANCES Open grid "duckboard" design with textured surface.

COLOURS Available in homogenous standard colour; Black. Other colours available on request.

DURABILITY One piece welded construction for maintenance free life.

WORKABILITY Flexible construction is easy to cut and shape on site.

Supplied in rolls with top ribs facing outwards. Requires inverting once rolled out prior to use.

USES All medium indoor & outdoor locations.

TECHNICAL DATA

ACOUSTIC Excellent sound absorption properties.

CHEMICAL Resistant to most acids, alkalines and oils. For specific chemical resistances, see

www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf

COMPOSITION Flexible DINP plasticised Polyvinyl Chloride (PVC).

ENVIRONMENT Made from post-industrial recycled PVC, always with a minimum content of 30% up to 100%.

Plastex does not use any substances currently included in the SVHC (Substances of Very High Concern) list under R.E.A.C.H.* in any matting products. All PVC grid products are 100% recyclable.

* Registration, Evaluation, Authorisation and Restriction of CHemical substances

FIRE DIN 4102 Part 1- Classification B2

HYGIENE Non-porous 100% PVC - Inhibits the growth of bacteria.

REVERSION Thermoplastic shrinkage can result in size reductions up to 2%. Accelerated in hot environments. Refer to

www.plastexmatting.com/uploads/4/4/0/0/44003899/vinyl-matting-dimensional-stability.pdf

SLIP RESISTANCE ASTM F 1677 - Dry/Wet: 0.6/0.6

DIN 51130: R11, V10

THERMAL Functional -23°C +60°C (slight size variation may occur at temperature extremes).

UV LIGHT Resistance to PVC degradation.

WARRANTY 2 years. See www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf




2

Web: www.plastexmatting.com

PRODUCT DATA SHEET: HERONAIR

ANCILLARIES



10mm x 50mm x 10.1m (3/8" x 2" x 33'))



10.5mm x 2.5m (13/32" x 8'2")

50 PVC edging strip

Supplied in rolls of 10.1m (33') length with cold welding paste.

Colours: Black, Dark Grey

Snap Track Low Profile

2 part snap track can be welded to join rolls end to end or side to side for large area covering. Supplied with cold welding paste.

Colours: Black, Dark Grey



Connector clips - Dual purpose

For joining sections of matting together side to side or end to end. Supplied in packs of 10.

Web: www.plastexmatting.com

