


PRODUCT DATA SHEET: VYNAGRIP


Jul-18

SIZES & WEIGHTS

	All dimensions are nominal		Height (mm)	Lengths (m)	Widths (cm)		Weight (kg/m ²)
	Tolerances (mm)		+/- 0.5	0+0.3	+/- 1		
Vynagrip	15	5 & 10	60	91	122	7.6	
Vynagrip Plus	15	10	60	91	122	7.6	



Vynagrip



Vynagrip Plus

GENERAL

APPEARANCES

Open grid "duckboard" design with textured surface.

COLOURS

Vynagrip: Available in homogenous standard colours; Red, Blue, Black.

Vynagrip Plus: Available in homogenous standard colour; Black with 5cm yellow bands to either side.

DURABILITY

One piece welded construction for maintenance free life.

WORKABILITY

Available in rolls for ease of installation. Easy to cut to size and shape.

Supplied in rolls with top ribs facing outwards. Requires inverting once rolled out prior to use.

USES

Heavy duty applications, both indoor and outside. Red colour is not colourfast in direct sunlight.

TECHNICAL DATA

ACOUSTIC

Excellent sound absorption properties.

ANTI-FATIGUE

University of Hertfordshire 1997; Evaluation of Anti Fatigue properties by self reports, sustained attention and electromyography measurements.

CHEMICAL

Resistant to most acids, alkalines and oils. For specific chemical resistances, see www.plastexmatting.com/uploads/4/4/0/0/44003899/pvc-chemical-resistance.pdf

COMPOSITION

Flexible DINP plasticised Polyvinyl Chloride (PVC).

ELECTRICAL

BS 2782: Part 2 Method 230A Insulation resistance > 2000M Ω Electric strength

ENVIRONMENT

Black colour is manufactured with our post industrial recycled material. Plastex does not use any substances currently included in the SVHC (Substances of Very High Concern) list under R.E.A.C.H.* in any matting products. All products are 100% recyclable.

* Registration, Evaluation, Authorisation and Restriction of Chemical substances

FIRE

EN ISO 13501 - I : 2007 - CfI - S1

HYGIENE

Non-porous 100% PVC - Inhibits the growth of bacteria.

REVERSION

Thermoplastic shrinkage can result in size reductions up to 2%. Accelerated in hot environments. Refer to www.plastexmatting.com/uploads/4/4/0/0/44003899/vinyl-matting-dimensional-stability.pdf

SLIP RESISTANCE

ASTM F 1677 - Dry/Wet: 1.0/0.9
DIN 51130: R11, V10

THERMAL

Functional -23°C +60°C (slight size variation may occur at temperature extremes).

UV LIGHT

Resistance to PVC degradation*.
*Red colour is not colourfast in direct sunlight.

WARRANTY

4 years. See www.plastexmatting.com/uploads/4/4/0/0/44003899/warranty.pdf




Plastic Extruders Ltd, Russell Gardens, Wickford, SS11 8DN, UK
Tel: +44(0)1268 571116

Web: www.plastexmatting.com

PRODUCT DATA SHEET: VYNAGRIP


ANCILLARIES



60mm PVC edging strip
Supplied in rolls of 10.1m (33') length with cold welding paste.
Colours: Black, Dark Grey, Dark Brown, Holly Green, Oxford Blue, Yellow



Snap Track
2 part snap track can be welded to join rolls end to end or side to side for large area covering. Supplied with cold welding paste.
Colours: Black, Dark Grey



100mm PVC edging strip
Supplied in rolls of 10.1m (33') length with cold welding paste.
Colours: Black, Dark Grey, Yellow




Connector clips - Side to end
For joining sections of matting together side to end.
Supplied in packs of 10.



15mm x 45mm x 2m
(5/8" x 1 13/16" x 6'6")

45mm Aluminium edging strip
Supplied in sections of 2m (6'6") length with fixing screws and plugs.
Colours: Anodised Aluminium, Powder Coated Yellow



Connector clips - Dual purpose
For joining sections of matting together side to side or end to end. Supplied in packs of 10.



Small floor hook
For securing sections of matting to floor.
Supplied in packs of 10 with screws and plugs.




Large floor hook
For securing sections of matting to floor.
Supplied in packs of 10 with screws and plugs.

PRODUCT DATA SHEET: VYNAGRIP MODULES

SIZES & WEIGHTS

<i>All dimensions are nominal</i>	Standard module options		Weight (kg/m ²)
<i>Tolerances (mm)</i>	<i>0+0.5</i>		
Vynagrip Modules	1.2 x 0.8m	1.5 x 1m	7.6



APPEARANCES

Open grid "duckboard" design with textured surface.

COLOURS

Available in homogenous standard colours; Black with Grey edging and Black with Yellow edging.

DURABILITY

One piece welded construction for maintenance free life.

WORKABILITY

Available in standard size modules with fitted edging on 3 sides.

USES

Work stations with likelihood of spillages.

For technical data, please refer to page 2



Plastic Extruders Ltd, Russell Gardens, Wickford, SS11 8DN, UK
Tel: +44(0)1268 571116

Web: www.plastexmatting.com