

STYLE REF: VX950A

STYLE NAME: ONYX BLACK

Rock Fall[®]
INDUSTRY DEFINING SAFETY FOOTWEAR

WOMENS

SPECIFICATION: EN ISO 20345:2011 S3 HI WR HRO SRC | UK 3-8 (WHOLE SIZES) | COLOUR: BLACK

100% NON-METALLIC, WITH PROTECTIVE TOECAP AND MIDSOLE, ONYX IS COMFORTABLE AND LIGHTWEIGHT, IT'S DEVELOPED WITH SPECIALIST DURABILITY MATERIALS INCLUDING AN ACTIV-TEX[®] WATERPROOF MEMBRANE AND SHOCK ABSORBING SOLID NITRILE RUBBER OUTSOLE. THE ROCK FALL WOMENS RANGE IS MADE ON A WOMENS SHOE MOULD MAKING IT MORE SLENDER AND BETTER FITTING.

VX950A



ACTIV-TEX

Upper Material

Water repellent full grain black leather

Protective Components

Protective fibreglass toecap and composite anti-penetration flexi-midsole

Lining Materials

Activ-Tex[®] waterproof and breathable bootie membrane - tested for 8 hours (5 times longer than EN requirement)

Scuff Cap and Outsole

Womens fitting shock absorbing nitrile rubber outsole

Footbed

Anti-fatigue EVA footbed

SUBJECT TO CHANGE WITHOUT PRIOR NOTICE: 01/06/2019

WWW.ROCKFALL.COM | WWW.ROCKFALL.COM/PRODUCTS/ONYX-BLACK

PROUDLY MANUFACTURED BY ROCK FALL UK, MAJOR HOUSE, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS

EU TYPE EXAMINATION CERTIFICATE

intertek



APPROVED BODY 0362

The safety footwear detailed herein meets the criteria of an EU Type Examination in accordance with Annex V, including the applicable clauses of the Essential Health and Safety Requirements of the PPE Regulation EU 2016/425 for Category II products.

This has been shown through satisfactory testing to EN ISO 20345: 2011 and examination of the Technical File Documentation.

Following an EU Declaration of Product Conformity you are hereby licensed to mark the product(s) detailed in accordance with Article 17 of the PPE Regulation EU 2016/425

ITS Testing Services (UK) Ltd.
Centre Court
Meridian Business Park
Leicester, LE19 1WD
United Kingdom
Phone: +44 (0)116 263 0330
Fax: +44 (0)116 263 0311

Issued to : ROCK FALL UK LTD.
WIMSEY WAY ALFRETON TRADING ESTATE,
DERBYSHIRE U.K. DE55 4LS

Issue Date : 15 July 2019

Expiry Date : 15 July 2024

Certificate No. : LECFI00375656

Product Reference(s) : ROCK FALL VX950A ONYX
ROCK FALL VX950C ONYX

Description : Construction : Cemented
Toecap : PEP Composite
Midsole : PEP Composite
Last : #PEP-PL
Sole : 2061# RB
Test Report(s) : See Technical File
Size Range : 3-13#
Category : S3 WR HRO SRC



Assessor:  Date: 15/07/2019

Certification Manager:  Date: 15/07/2019

For and on behalf of ITS Testing Services (UK) Limited

EU DECLARATION OF CONFORMITY

Rock Fall UK, Major House,
Unit 1/3, Wimsey Way,
Alfreton, Derbyshire, DE55 4LS
United Kingdom
Tel: **01773 608616**
Email: **sales@rockfall.com**
rockfall.com

The manufacturer or his nominated representative established in the community;

ROCK FALL UK LTD, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS, UNITED KINGDOM

Declares that the PPE described hereafter;

ROCK FALL VX950A Onyx Black

Is in conformity with the provisions of PPE Regulation EU 2016/425 for **Category II** and, where such is the case, with the national standard transposing the union harmonised standard no. **EN ISO 20345:2011**

This declaration of conformity is issued under the sole responsibility of the manufacturer;

ROCK FALL UK LTD, WIMSEY WAY, ALFRETON, DERBYSHIRE, DE55 4LS, UNITED KINGDOM

Is identical to the PPE submitted to: **ITS testing Services (UK) Ltd, Centre Court, Meridian Business Park, Leicester, LE19 1WD, United Kingdom. Approved Body 0362.** who performed the Eu type examination (Module B) and issued the EU type -examination certificate: **LECF100375656**

The PPE is subject to the procedure set out in **Module C2** of the PPE Regulation EU 2016/425 under the supervision of the notified body:


ITS testing Services (UK) Ltd, Centre Court, Meridian Business Park, Leicester, LE19 1WD, United Kingdom. Approved Body 0362

Signature:

A handwritten signature in black ink, appearing to read "R. Kinson".

Position: Director

Date: 1/07/2019



Test Report

Tests Conducted (As Requested By The Applicant)

Number: GZHT90492559

Slip Resistance (EN ISO 20344:2011(5.11) & ISO 13287:2012, SRA, Temperature: 23°C)

			<u>Requirement</u>	<u>Pass/Fail</u>
<u>Size 36</u>	Right	On Eurotile 2 With NaLS		
		Forward Heel Slip (#1): 0.33	Min. 0.28	Pass
		Forward Flat Slip (#2): 0.34	Min. 0.32	Pass
<u>Size 42</u>	Right	On Eurotile 2 With NaLS		
		Forward Heel Slip (#1): 0.34	Min. 0.28	Pass
		Forward Flat Slip (#2): 0.35	Min. 0.32	Pass
<u>Size 47</u>	Right	On Eurotile 2 With NaLS		
		Forward Heel Slip (#1): 0.35	Min. 0.28	Pass
		Forward Flat Slip (#2): 0.35	Min. 0.32	Pass

Note:

It Must Be Noted That The Slip Resistance Test Carried Out In This Report Denotes An Indication Of Slip Of This Particular Footwear/Component On The Surface Mentioned In The Test Item. It Is Important To Note That Footwear Is Subject To Many Different Conditions Encountered In Everyday Use And That It Is Impossible To Make Footwear Resistant To Slip In All Conditions. Nevertheless, It Is Generally Accepted That Problems Are Minimized If The Guideline Coefficients Of Friction Are Achieved.

Remark:

- #1 = Using Standard Shoemaking Last
- #2 = Using Mechanical Foot

Expanded Uncertainty: 0.01, With K = 2.03 At 95% Confidence Level.

This report is made solely on the basis of your instructions and/or information and materials supplied by you. It is not intended to be a recommendation for any particular course of action. Intertek does not accept a duty of care or any other responsibility to any person other than the Client in respect of this report and only accepts liability to the Client insofar as is expressly contained in the terms and conditions governing Intertek's provision of services to you. Intertek makes no warranties or representations either express or implied with respect to this report save as provided for in those terms and conditions. We have aimed to conduct the Review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or wilful misconduct.



中国认可
国际互认
检测
TESTING
CNAS L0220

Number: GZHT90593751

Test Report

Tests Conducted (As Requested By The Applicant)

6 Slip Resistance (EN ISO 20344:2011(5.11) & ISO 13287:2012, SRB, Temperature: 23°C)

Sample	Size	Test Floor	Lubricant	Modes	Results	Requirement	Pass/Fail
-	36 (Left)	Steel Floor	Glycerine	Forward Heel Slip (#1)	0.16	Min. 0.13	Pass
				Forward Flat Slip (#2)	0.23	Min. 0.18	Pass
	42 (Left)	Steel Floor	Glycerine	Forward Heel Slip (#1)	0.18	Min. 0.13	Pass
				Forward Flat Slip (#2)	0.23	Min. 0.18	Pass
	47 (Left)	Steel Floor	Glycerine	Forward Heel Slip (#1)	0.19	Min. 0.13	Pass
				Forward Flat Slip (#2)	0.25	Min. 0.18	Pass

Note:

It Must Be Noted That The Slip Resistance Test Carried Out In This Report Denotes An Indication Of Slip Of This Particular Footwear/Component On The Surface Mentioned In The Test Item. It Is Important To Note That Footwear Is Subject To Many Different Conditions Encountered In Everyday Use And That It Is Impossible To Make Footwear Resistant To Slip In All Conditions. Nevertheless, It Is Generally Accepted That Problems Are Minimized If The Guideline Coefficients Of Friction Are Achieved.

Remark: #1 = Using Standard Shoemaking Last
#2 = Using Mechanical Foot

Expanded Uncertainty: 0.01, With K = 2.03 At 95% Confidence Level.