## Elipse P3 Respirator

The ELIPSE P3 R carries the highest classification for a particulate filter. EN143 requires the efficiency to be at least 99.95%. The ELIPSE P3 R achieved 99.98% at 0.3 micron.

It is perfect for everyday use from DIY and commercial construction through to the more demanding environments of metalworking, welding and stonemasonry.

Replacement filters available.

## Features & Benefits>

- > Approved to European Standard EN140: 1998. APF 20
- > Elipse twin filter ready to wear half mask
- > Latex and silicone free, lightweight TPE face piece that is comfortable to wear for long periods of time
- > Low profile filters provide unobstructed field of vision
- > Compatible with other PPE safety products including visors and welding helmets



PRODUCT CODE	DESCRIPTION
SPR299	Elipse P3 Respirator S/M
SPR316	Elipse P3 Filter Kit
SPR501	Elipse P3 Respirator M/L

Product code SPR501

Description Elipse P3 replaceable filters ready to use Respirator

M/L

Materials of construction

Mask Body: TPE (Thermo Plastic Elastomer)

Filter media HESPA (High Efficiency Synthetic Particulate Air

filter)

Pore size  $(\mu m)$  0.3

Dimension 93 x 130 x 110 mm

Weight (g) Mask + Filter: 132 g, Mask body: 97.6 g

Retention range 99.95% (minimum efficiency)

Ref. standard EN140, EN143 Temperature -5°C +55°C

Notes Half-mask for protection from dust, metal fumes, oil

and water mists and micro-organisms, i.e. bacteria and viruses