# TECHNICAL SPECIFICATION



# Typhoon™ Moulded Mask FFP3 Valved (735)

Box of 10 / BEK136-101-A00



## DESCRIPTION

Moulded mask featuring our unique Typhoon™ Valve technology for extremely low exhale breathing resistance, and low CO2, heat and moisture build up.

• High efficiency (99% minimum) filtering

# OPTIONS

Box of 10 (BEK136-101-A00)

## SAFETY STANDARDS

EN 149







Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com







#### **SPECIFICATIONS**

Classification

FFP3 (Filtering Facepiece Particulate)

NR (Non-Reusable)



Activated Carbon Layer

Maximum Total Inward Leakage (TIL)

2%

**UK Assigned Protection Factor** 

20



Exhalation Valve

Yes - JSP Typhoon Valve



Nose Bridge

Adjustable Aluminium

Metal Free

No

Filter Shelf Life

5 Years



**Product Weight** 

29g



P (Protects Against Solid and Liquid Aerosols)



(D) Resistance to dust clogging

Yes - D marking = passes optional clogging test

Minimum Filtration Efficiency

99% For FFP3 Rated

Nominal Protection Factor

50

Mask Design

Moulded

Buckle Type Harness adjustment system

Latex free

Yes

Mask Material

Polypropylene



**BSI Kitemark** 

Yes

#### **FEATURES**



#### Comfort

A 360° comfort foam area around the inside of the mask provides a perfect fit and maximum resistance.



Fit

The welded nose piece prevents any irritation, misshaping and gives a tighter fit. Adjustable strap means it can be fitted comfortably to all head sizes and shapes.



#### Typhoon™ Valve

The Unique Typhoon™ valve has been designed to reduce breathing resistance, heat and moisture build-up. The valve is unaffected by any moisture, and therefore can be used with the same performance under very low temperatures.

# RANGE



# DOWNLOADS



Image Pack (ZIP)







JSP Limited. Worsham Mill. Minster Lovell. Oxford OX29 0TA. England.

Tel: +44 (0)1993 826050 / Fax: +44 (0)1993 824411 / Email: sales@jspsafety.com / Web: www.jspsafety.com

Do Not Publish without written permission from JSP Limited. Contact copyright@jspsafety.com. Information correct in the United Kingdom at date of issue and may be subject to change. Any third-party machine and automated translations processed by users may have inaccuracies and should not be relied upon.



